

# FIDO Metadata Statement

Review Draft, January 05, 2026

 REVIEW DRAFT

**This version:**

<https://fidoalliance.org/specs/mds/fido-metadata-statement-v3.1.1-rd02-20260105>

**Issue Tracking:**

[GitHub](#)

**Editors:**

[Billy Jack](#) (Microsoft)

[Rolf Lindemann](#) (Nok Nok Labs)

**Former Editor:**

[Yuriy Ackermann](#) (FIDO Alliance)

Copyright © 2026 [FIDO Alliance](#). All Rights Reserved.

---

## Abstract

FIDO authenticators may have many different form factors, characteristics and capabilities. This document defines a standard means to describe the relevant pieces of information about an authenticator in order to interoperate with it, or to make risk-based policy decisions about transactions involving a particular authenticator.

## Status of This Document

*This section describes the status of this document at the time of its publication. Other documents may supersede this document. A list of current FIDO Alliance publications and the latest revision of this technical report can be found in the [FIDO Alliance specifications index](#) at <https://fidoalliance.org/specifications/>.*

This document was published by the [FIDO Alliance](#) as a Review Draft Specification. This document is intended to become a FIDO Alliance Proposed Standard. If you wish to make comments regarding this document, please [Contact Us](#). All comments are welcome.

**This is a Review Draft Specification and is not intended to be a basis for any implementations as the Specification may change.** Permission is hereby granted to use the Specification solely for the purpose of reviewing the Specification. No rights are granted to prepare derivative works of this Specification. Entities seeking permission to reproduce portions of this Specification for other uses must contact the FIDO Alliance to determine whether an appropriate license for such use is available.

Implementation of certain elements of this Specification may require licenses under third party intellectual property rights, including without limitation, patent rights. The FIDO Alliance, Inc. and its Members and any other contributors to the Specification are not, and shall not be held, responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

THIS FIDO ALLIANCE SPECIFICATION IS PROVIDED “AS IS” AND WITHOUT ANY WARRANTY OF ANY KIND, INCLUDING, WITHOUT LIMITATION, ANY EXPRESS OR IMPLIED WARRANTY OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Table of Contents

### 1 Notation

|          |                 |
|----------|-----------------|
| <b>2</b> | <b>Overview</b> |
| 2.1      | Scope           |
| 2.2      | Audience        |
| 2.3      | Architecture    |

### **3 Types**

|      |   |
|------|---|
| 3.1  | Authenticator Attestation GUID (AAGUID) typedef |
| 3.2  | CodeAccuracyDescriptor dictionary               |
| 3.3  | BiometricAccuracyDescriptor dictionary          |
| 3.4  | PatternAccuracyDescriptor dictionary            |
| 3.5  | VerificationMethodDescriptor dictionary         |
| 3.6  | VerificationMethodANDCombinations typedef       |
| 3.7  | rgbPaletteEntry dictionary                      |
| 3.8  | DisplayPNGCharacteristicsDescriptor dictionary  |
| 3.9  | EcdaaTrustAnchor dictionary                     |
| 3.10 | ExtensionDescriptor dictionary                  |
| 3.11 | FriendlyNames dictionary                        |
| 3.12 | AlternativeDescriptions dictionary              |
| 3.13 | AuthenticatorGetInfo dictionary                 |

### **4 Metadata Keys**

|     |                  |
|-----|------------------|
| 4.1 | SVG requirements |
|-----|------------------|

### **5 Metadata Statement Format**

|     |               |
|-----|---------------|
| 5.1 | UAF Example   |
| 5.2 | U2F Example   |
| 5.3 | FIDO2 Example |

### **6 Additional Considerations**

|     |                            |
|-----|----------------------------|
| 6.1 | Field updates and metadata |
|-----|----------------------------|

### **Index**

Terms defined by this specification

Terms defined by reference

### **References**

|                        |
|------------------------|
| Normative References   |
| Informative References |

### **IDL Index**

## **1. Notation**

Type names, attribute names and element names are written as code.

String literals are enclosed in "", e.g. "UAF-TLV".

In formulas we use "|" to denote byte wise concatenationoperations.

DOM APIs are described using the ECMAScript[\[ECMA-262\]](#) bindings for WebIDL [\[WebIDL-ED\]](#).

Following [\[WebIDL-ED\]](#), dictionary members are optional unless they are explicitly marked as required.

WebIDL dictionary members MUST NOT have a value of null.

Unless otherwise specified, if a WebIDL dictionary member is DOMString, it MUST NOT be empty.

Unless otherwise specified, if a WebIDL dictionary member is a List, it MUST NOT be an empty list.

All diagrams, examples, notes in this specification are non-normative.

Note: Certain dictionary members need to be present in order to comply with FIDO requirements. Such members are marked in the WebIDL definitions found in this document, as required. The keyword required has been introduced by [\[WebIDL-ED\]](#), which is a work-in-progress. If you are using a WebIDL parser which implements [\[WebIDL\]](#), then you may remove the keyword required from your WebIDL and use other means to ensure those fields are present.

DOM APIs are described using the ECMAScript[\[ECMA-262\]](#) bindings for WebIDL [\[WebIDL-ED\]](#).

## 2. Overview§

*This section is not normative.*

The FIDO family of protocols enable simpler and more secure online authentication utilizing a wide variety of different devices in a competitive marketplace. Much of the complexity behind this variety is hidden from Relying Party applications, but in order to accomplish the goals of FIDO, Relying Parties must have some means of discovering and verifying various characteristics of authenticators. Relying Parties can learn a subset of verifiable information for authenticators certified by the FIDO Alliance with an Authenticator Metadata statement. The Metadata statement can be acquired from the Metadata BLOB that is hosted on the Metadata Service [\[FIDOMetaDataService\]](#).

For definitions of terms, please refer to the FIDO Glossary[\[FIDOGlossary\]](#).

### 2.1. Scope§

This document describes the format of and information contained in *Authenticator Metadata* statements. For a definitive list of possible values for the various types of information, refer to the FIDO Registry of Predefined Values [\[FIDORRegistry\]](#).


The description of the processes and methods by which authenticator metadata statements are distributed and the methods how these statements can be verified are described in the Metadata Service Specification [\[FIDOMetadataService\]](#).

### 2.2. Audience§

The intended audience for this document includes:

- FIDO authenticator vendors who wish to produce metadata statements for their products.
- FIDO server implementers who need to consume metadata statements to verify characteristics of authenticators and attestation statements, make proper algorithm choices for protocol messages, create policy statements or tailor various other modes of operation to authenticator-specific characteristics.
- FIDO relying parties who wish to
  - create custom policy statements about which authenticators they will accept
  - risk score authenticators based on their characteristics
  - verify attested authenticator IDs for cross-referencing with third party metadata

### 2.3. Architecture§



**Figure 1** The FIDO Architecture

*Authenticator metadata statements* are used directly by the FIDO server at a relying party, but the information contained in the authoritative statement is used in several other places. How a server obtains these metadata statements is described in [\[FIDOMetadataService\]](#).

The workflow around an authenticator metadata statement is as follows:

1. The authenticator vendor produces a metadata statement, that is UTF-8 encoded, describing the characteristics of an authenticator.
2. The metadata statement is submitted to the FIDO Alliance as part of the FIDO certification process. The FIDO Alliance distributes the metadata as described in [\[FIDOMetadataService\]](#).
3. A FIDO relying party configures its registration policy to allow authenticators matching certain characteristics to be registered.
4. The FIDO server sends a registration challenge message. This message can contain such policy statement.
5. Depending on the FIDO protocol being used, either the relying party application or the FIDO UAF Client receives the policy statement as part of the challenge message and processes it. It queries available authenticators for their self-reported characteristics and (with the user's input) selects an authenticator that matches the policy, to be registered.
6. The client processes and sends a registration response message to the server. This message contains a reference to the authenticator model and, optionally, a signature made with the private key corresponding to the public key in the authenticator's attestation certificate.
7. The FIDO Server looks up the metadata statement for the particular authenticator model. If the metadata statement lists an attestation certificate(s), it verifies that an attestation signature is present, and made with the private key corresponding to either (a) one of the certificates listed in this metadata statement or (b)

corrsponding to the public key in a certificate that *chains* to one of the issuer certificates listed in the authenticator's metadata statement.

8. The FIDO Server next verifies that the authenticator meets the originally supplied registration policy based on its authoritative metadata statement. This prevents the registration of unexpected authenticator models.
9. *Optionally*, a FIDO Server may, with input from the Relying Party, assign a risk or trust score to the authenticator, based on its metadata, including elements not selected for by the stated policy.
10. *Optionally*, a FIDO Server may cross-reference the attested authenticator model with other metadata databases published by third parties. Such third-party metadata might, for example, inform the FIDO Server if an authenticator has achieved certifications relevant to certain markets or industry verticals, or whether it meets application-specific regulatory requirements.

### 3. Types§

*This section is normative.*

#### 3.1. Authenticator Attestation GUID (AAGUID) `typedef`§

```
typedef DOMString AAGUID;  
  
string[36]
```

Some authenticators have an AAGUID, which is a 128-bit identifier that indicates the type (e.g. make and model) of the authenticator. The AAGUID MUST be chosen by the manufacturer to be identical across all substantially identical authenticators made by that manufacturer, and different (with probability  $1-2^{-128}$  or greater) from the AAGUIDs of all other types of authenticators.

The AAGUID is represented as a string (e.g. "7a98c250-6808-11cf-b73b-00aa00b677a7") consisting of 5 hex strings separated by a dash ("‐"), see [\[RFC4122\]](#).

#### 3.2. CodeAccuracyDescriptor `dictionary`§

The `CodeAccuracyDescriptor` describes the relevant accuracy/complexity aspects of passcode user verification methods.

One example of such a method is the use of 4 digit PIN codes for mobile phone SIM card unlock.

We are using the numeral system base (radix) and `minLen`, instead of the number of potential combinations since there is sufficient evidence [\[iPhonePasscodes\]](#) [\[MoreTopWorstPasswords\]](#) that users don't select their code evenly distributed at random. So software might take into account the various probability distributions for different bases. This essentially means that in practice, passcodes are not as secure as they could be if randomly chosen.

```
dictionary CodeAccuracyDescriptor {  
    required unsigned short base;  
    required unsigned short minLength;  
    unsigned short maxRetries;  
    unsigned short blockSlowdown;  
};
```

##### **base, of type `unsigned short`**

The numeric system base (radix) of the code, e.g. 10 in the case of decimal digits.

#### **minLength, of type [unsigned short](#)**

The minimum number of digits of the given base required for that code, e.g. 4 in the case of 4 digits.

#### **maxRetries, of type [unsigned short](#)**

Maximum number of false attempts before the authenticator will block this method (at least for some time). 0 means it will never block.

#### **blockSlowdown, of type [unsigned short](#)**

Enforced minimum number of seconds wait time after blocking (e.g. due to forced reboot or similar). 0 means this user verification method will be blocked, either permanently or until an alternative user verification method succeeded. All alternative user verification methods MUST be specified appropriately in the Metadata in userVerificationDetails.

### 3.3. BiometricAccuracyDescriptor dictionary§

The BiometricAccuracyDescriptor describes relevant accuracy/complexity aspects in the case of a biometric user verification method, see [\[FIDOBiometricsRequirements\]](#).

At least one of the values MUST be set. If the vendor doesn't want to specify such values, then VerificationMethodDescriptor.baDesc MUST be omitted.

Note: Typical fingerprint sensor characteristics can be found in Android [\[AndroidCompatibilityDefinition\]](#) and Apple iOS [\[ApplePlatformSecurity\]](#).

```
dictionary BiometricAccuracyDescriptor {  
    double      selfAttestedFRR;  
    double      selfAttestedFAR;  
    double      iAPARThreshold;  
    unsigned short maxTemplates;  
    unsigned short maxRetries;  
    unsigned short blockSlowdown;  
};
```

#### **selfAttestedFRR, of type [double](#)**

The false rejection rate [\[ISOIEC-19795-1\]](#) for a single template, i.e. the percentage of verification transactions with truthful claims of identity that are incorrectly denied. For example a FRR of 10% would be encoded as 0.1.

This value is self attested and, if the authenticator passed biometric certification, the data is an independently verified FRR as measured when meeting the FRR target specified in the biometric certification requirements [\[FIDOBiometricsRequirements\]](#) for the indicated biometric certification level (see certLevel in related biometricStatusReport as specified in [\[FIDOMetadataService\]](#)).

Note: The false rejection rate is relevant for user convenience. Lower false rejection rates mean better convenience.

#### **selfAttestedFAR, of type [double](#)**

The false acceptance rate [\[ISOIEC-19795-1\]](#) for a single template, i.e. the percentage of verification transactions with wrongful claims of identity that are incorrectly confirmed. For example a FAR of 0.002% would be encoded as 0.00002.

This value is self attested and, if the authenticator passed biometric certification, the data is an independently verified FAR specified in the biometric certification requirements [\[FIDOBiometricsRequirements\]](#) for the indicated biometric certification level (see certLevel in related biometricStatusReport as specified in [\[FIDOMetadataService\]](#)).

Note: The resulting FAR when all templates are used is approx. `maxTemplates * FAR`.

The false acceptance rate is relevant for the security. Lower false acceptance rates mean better security.

Only the live captured subjects are covered by this value - not the presentation of artefacts.

#### **iAPARThreshold, of type [double](#)**

Impostor Attack Presentation Accept Rate (IAPAR) is the proportion of impostor attack presentations using the same presentation attack instrument (PAI) species that result in accept [\[Isoiec-30107-3\]](#). For biometric certification requirements [\[FIDOBiometricsRequirements\]](#), certification can be achieved for an IAPAR threshold of less than 7% OR less than 15% for each of the PAI species tested.

If the authenticator did not pass biometric certification, vendor can submit any number, but this number has not been validated for biometric performance requirements.

#### **maxTemplates, of type [unsigned short](#)**

Maximum number of alternative templates from different fingers allowed (for other modalities, multiple parts of the body that can be used interchangeably), e.g. 3 if the user is allowed to enroll up to 3 different fingers to a fingerprint based authenticator.

If the authenticator passed biometric certification this value defaults to 1. For maxTemplates greater than one, it SHALL be independently verified to ensure FAR meets biometric performance requirements of certLevel (of the related biometricStatusReport as specified in [\[FIDOMetadataService\]](#)).

If the authenticator did not pass biometric certification, vendor can submit any number, but this number has not been validated for biometric performance requirements.

#### **maxRetries, of type [unsigned short](#)**

Maximum number of false attempts before the authenticator will block this method (at least for some time). 0 means it will never block.

#### **blockSlowdown, of type [unsigned short](#)**

Enforced minimum number of seconds wait time after blocking (e.g. due to forced reboot or similar). 0 means that this user verification method will be blocked either permanently or until an alternative user verification method succeeded. All alternative user verification methods MUST be specified appropriately in the metadata in `userVerificationDetails`.

### **3.4. PatternAccuracyDescriptor dictionary**

The `PatternAccuracyDescriptor` describes relevant accuracy/complexity aspects in the case that a pattern is used as the user verification method.

Note: One example of such a pattern is the 3x3 dot matrix as used in Android [\[AndroidUnlockPattern\]](#) screen unlock. The `minComplexity` would be 1624 in that case, based on the user choosing a 4-digit PIN, the minimum allowed for this mechanism.

```
dictionary PatternAccuracyDescriptor {
    required unsigned long minComplexity;
    unsigned short maxRetries;
    unsigned short blockSlowdown;
};
```

#### **minComplexity, of type [unsigned long](#)**

Number of possible patterns (having the minimum length) out of which exactly one would be the right one, i.e. 1/probability in the case of equal distribution.

#### **maxRetries, of type [unsigned short](#)**

Maximum number of false attempts before the authenticator will block authentication using this method (at least temporarily). 0 means it will never block.

### **blockSlowdown, of type unsigned short**

Enforced minimum number of seconds wait time after blocking (due to forced reboot or similar mechanism).

0 means this user verification method will be blocked, either permanently or until an alternative user verification method succeeded. All alternative user verification methods MUST be specified appropriately in the metadata under `userVerificationDetails`.

## **3.5. VerificationMethodDescriptor dictionary**

A descriptor for a specific *base user verification method* as implemented by the authenticator.

A base user verification method must be chosen from the list of those described in [\[FIDORRegistry\]](#).

**Note:** In reality, several of the methods described above might be combined. For example, a fingerprint based user verification can be combined with an alternative password.

The specification of the related `AccuracyDescriptor` is optional, but recommended.

```
dictionary VerificationMethodDescriptor {
    DOMString           userVerificationMethod;
    CodeAccuracyDescriptor  caDesc;
    BiometricAccuracyDescriptor  baDesc;
    PatternAccuracyDescriptor  paDesc;
};
```

### **userVerificationMethod, of type DOMString**

a single `USER_VERIFY` constant case-sensitive string name. See section "User Verification Methods" in [\[FIDORRegistry\]](#) (e.g. "presence\_internal"). This value MUST NOT be empty.

The constant `USER_VERIFY_ALL` MUST NOT be used here.

### **caDesc, of type CodeAccuracyDescriptor**

May optionally be used in the case of method `USER_VERIFY_PASSCODE_INTERNAL` or `USER_VERIFY_PASSCODE_EXTERNAL`.

### **baDesc, of type BiometricAccuracyDescriptor**

May optionally be used in the case of method `USER_VERIFY_FINGERPRINT_INTERNAL`, `USER_VERIFY_VOICEPRINT_INTERNAL`, `USER_VERIFY_FACEPRINT_INTERNAL`, `USER_VERIFY_EYEPRINT_INTERNAL`, or `USER_VERIFY_HANDPRINT_INTERNAL`.

### **paDesc, of type PatternAccuracyDescriptor**

May optionally be used in case of method `USER_VERIFY_PATTERN_INTERNAL` or `USER_VERIFY_PATTERN_EXTERNAL`

## **3.6. VerificationMethodANDCombinations typedef**

```
typedef VerificationMethodDescriptor[] VerificationMethodANDCombinations;
```

`VerificationMethodANDCombinations` list describes a combination of the user verification methods that MUST be passed by the user, in order to achieve successful user verification.

The list MUST NOT be empty.

Each entry in the `VerificationMethodANDCombinations` describes an individual user verification method, that must be passed by the user, as well as some security properties of the user verification method such as pin requirements, biometric properties, etc

### 3.7. `rgbPaletteEntry` dictionary§

The `rgbPaletteEntry` is an RGB three-sample tuple palette entry

```
dictionary rgbPaletteEntry {
    required unsigned short r;
    required unsigned short g;
    required unsigned short b;
};
```

#### **r, of type unsigned short**

Red channel sample value

#### **g, of type unsigned short**

Green channel sample value

#### **b, of type unsigned short**

Blue channel sample value

### 3.8. `DisplayPNGCharacteristicsDescriptor` dictionary§

The `DisplayPNGCharacteristicsDescriptor` describes a PNG image characteristics as defined in the [PNG\[PNG\]](#) spec for IHDR (image header) and PLTE (palette table)

```
dictionary DisplayPNGCharacteristicsDescriptor {
    required unsigned long width;
    required unsigned long height;
    required octet          bitDepth;
    required octet          colorType;
    required octet          compression;
    required octet          filter;
    required octet          interlace;
    rgbPaletteEntry[]      plte;
};
```

#### **width, of type unsigned long**

image width

#### **height, of type unsigned long**

image height

#### **bitDepth, of type octet**

Bit depth - bits per sample or per palette index.

#### **colorType, of type octet**

Color type defines the PNG image type.

#### **compression, of type octet**

Compression method used to compress the image data.

#### **filter, of type octet**

Filter method is the preprocessing method applied to the image data before compression.

#### **interlace, of type octet**

Interlace method is the transmission order of the image data.

#### **plte, of type rgbPaletteEntry[]**

1 to 256 palette entries

### 3.9. `EcdaaTrustAnchor` dictionary§

In the case of ECDAA attestation, the ECDAA-Issuer's trust anchor MUST be specified in this field.

```
dictionary EcdaaTrustAnchor {
    required DOMString X;
    required DOMString Y;
    required DOMString c;
    required DOMString sx;
    required DOMString sy;
    required DOMString G1Curve;
};
```

#### X, of type [DOMString](#)

base64url encoding of the result of ECPoint2ToB of the ECPoint2 \(\mathbf{X} = \mathbf{P}\_2^{\mathbf{x}}\). See [\[FIDOEcdaaAlgorithm\]](#) for the definition of ECPoint2ToB.

#### Y, of type [DOMString](#)

base64url encoding of the result of ECPoint2ToB of the ECPoint2 \(\mathbf{Y} = \mathbf{P}\_2^{\mathbf{y}}\). See [\[FIDOEcdaaAlgorithm\]](#) for the definition of ECPoint2ToB.

#### c, of type [DOMString](#)

base64url encoding of the result of BigNumberToB(\(c\)). See section "Issuer Specific ECDA Parameters" in [\[FIDOEcdaaAlgorithm\]](#) for an explanation of \(\mathbf{c}\). See [\[FIDOEcdaaAlgorithm\]](#) for the definition of BigNumberToB.

#### sx, of type [DOMString](#)

base64url encoding of the result of BigNumberToB(\(sx\)). See section "Issuer Specific ECDA Parameters" in [\[FIDOEcdaaAlgorithm\]](#) for an explanation of \(\mathbf{sx}\). See [\[FIDOEcdaaAlgorithm\]](#) for the definition of BigNumberToB.

#### sy, of type [DOMString](#)

base64url encoding of the result of BigNumberToB(\(sy\)). See section "Issuer Specific ECDA Parameters" in [\[FIDOEcdaaAlgorithm\]](#) for an explanation of \(\mathbf{sy}\). See [\[FIDOEcdaaAlgorithm\]](#) for the definition of BigNumberToB.

#### G1Curve, of type [DOMString](#)

Name of the Barreto-Naehrig elliptic curve for G1. "BN\_P256", "BN\_P638", "BN\_ISOP256", and "BN\_ISOP512" are supported. See section "Supported Curves for ECDA" in [\[FIDOEcdaaAlgorithm\]](#) for details.

Note: Whenever a party uses this trust anchor for the first time, it must first verify that it was correctly generated by verifying \(\mathbf{(s, sx, sy)}\). See [\[FIDOEcdaaAlgorithm\]](#) for details.

## 3.10. ExtensionDescriptor dictionary [§](#)

This descriptor contains an extension supported by the authenticator.

```
dictionary ExtensionDescriptor {
    required DOMString id;
    unsigned short tag;
    DOMString data;
    required boolean fail_if_unknown;
};
```

#### id, of type [DOMString](#)

Identifies the extension.

#### tag, of type [unsigned short](#)

The TAG of the extension if this was assigned. TAGs are assigned to extensions if they could appear in an assertion.

Examples are TAG\_USER\_VERIFICATION\_STATE and TAG\_USER\_VERIFICATION\_INDEX as defined in [UAF Registry](#).

#### **data, of type [DOMString](#)**

Contains arbitrary data further describing the extension and/or data needed to correctly process the extension.

This field MAY be missing or it MAY be empty.

#### **fail\_if\_unknown, of type [boolean](#)**

Indicates whether unknown extensions must be ignored (false) or must lead to an error (true) when the extension is to be processed by the FIDO Server, FIDO Client, ASM, or FIDO Authenticator.

- A value of false indicates that unknown extensions MUST be ignored.
- A value of true indicates that unknown extensions MUST result in an error.

### **3.11. FriendlyNames dictionary**

This descriptor contains friendly names (e.g., public trade name) of the authenticator in multiple languages.

```
dictionary FriendlyNames {  
    DOMString *IETFLanguageCodes-members...;  
};
```

#### **\*IETFLanguageCodes-members...**

IETF language codes ([RFC5646](#)), defined by a primary language subtag, followed by a region subtag based on a two-letter country code from [ISO3166](#) alpha-2 (usually written in upper case), e.g: Austrian-German - "de-AT". In case of absence of the specific territorial language definition, vendor should fallback to the more general language option, e.g: If "de" is given, but "de-AT" is missing, the use "de" entry instead. Description values can contain any UTF-8 characters.

For example:

```
{  
    "en-US": "FIDO Sample Security Key"  
}
```

Each entry SHOULD NOT exceed a maximum length of 63 characters to ensure proper display.

### **3.12. AlternativeDescriptions dictionary**

This descriptor contains description in alternative languages.

```
dictionary AlternativeDescriptions {  
    DOMString *IETFLanguageCodes-members...;  
};
```

#### **\*IETFLanguageCodes-members...**

IETF language codes ([RFC5646](#)), defined by a primary language subtag, followed by a region subtag based on a two-letter country code from [ISO3166](#) alpha-2 (usually written in upper case), e.g: Austrian-German - "de-AT". In case of absence of the specific territorial language definition, vendor should fallback to the more general language option, e.g: If "de" is given, but "de-AT" is missing, the use "de" entry instead. Description values can contain any UTF-8 characters.

For example:

```

{
  "ru-RU": "Пример U2F аутентификатора от FIDO Alliance",
  "fr-FR": "Exemple U2F authenticator de FIDO Alliance"
}

```

Each description SHALL NOT exceed a maximum length of 200 characters.

### 3.13. AuthenticatorGetInfo dictionary§

This dictionary describes supported versions, extensions, AAGUID of the device and its capabilities.

```
dictionary AuthenticatorGetInfo {
  DOMString members...;
};
```

#### members...

The members are the fields of the structure reported by an authenticator when invoking the 'authenticatorGetInfo' method, see [\[FIDOCTAP\]](#). All binary values are base64 encoded.

## 4. Metadata Keys§

*This section is normative.*

```
dictionary MetadataStatement {
  DOMString
  AAID
  AAGUID
  DOMString[]
  FriendlyNames
  required DOMString
  AlternativeDescriptions
  required unsigned long
  required DOMString
  required unsigned short
  required Version[]
  required DOMString[]
  required DOMString[]
  required DOMString[]
  VerificationMethodANDCombinations[]
  required DOMString[]
  boolean
  boolean
  required DOMString[]
  unsigned short
  DOMString[]
  required DOMString[]
  DOMString
  DisplayPNGCharacteristicsDescriptor[]
  required DOMString[]
  EcdaaTrustAnchor[]
  DOMString
  DOMString
  DOMString
  DOMString
  ExtensionDescriptor[]
  DOMString
  AuthenticatorGetInfo
  DOMString
};

legalHeader;
aaid;
aaguid;
attestationCertificateKeyIdentifiers;
friendlyNames;
description;
alternativeDescriptions;
authenticatorVersion;
protocolFamily;
schema;
upv;
authenticationAlgorithms;
publicKeyAlgAndEncodings;
attestationTypes;
userVerificationDetails;
keyProtection;
isKeyRestricted;
isFreshUserVerificationRequired;
matcherProtection;
cryptoStrength;
attachmentHint;
tcDisplay;
tcDisplayContentType;
tcDisplayPNGCharacteristics;
attestationRootCertificates;
ecdaaTrustAnchors;
icon;
iconDark;
providerLogoLight;
providerLogoDark;
supportedExtensions;
multiDeviceCredentialSupport;
authenticatorGetInfo;
cxConfigURL;
```

### **legalHeader, of type [DOMString](#)**

The legalHeader, which must be in each Metadata Statement, is an indication of the acceptance of the relevant legal agreement for using the MDS.

The example of a Metadata Statement legal header is:

```
"legalHeader": "https://fidoalliance.org/metadata/metadata-statement-legal-header/"
```

### **aaid, of type [AAID](#)**

The Authenticator Attestation ID. See [UAFProtocol](#) for the definition of the AAID structure. This field MUST be set if the authenticator implements FIDO UAF.

Note: FIDO UAF Authenticators support AAID, but they don't support AAGUID.

It is always expected that the UAF Authenticator (or at least the UAF ASM) knows and provides the correct AAID.

### **aaguid, of type [AAGUID](#)**

The Authenticator Attestation GUID. See [FIDOKeyAttestation](#) for the definition of the AAGUID structure. This field MUST be set if the authenticator implements FIDO2.

Note: FIDO2 Authenticators support AAGUID, but they don't support AAID.

For credentials that are backup eligible, restoring them to a different authenticator model/passkey provider might be supported as well. The [AAGUID](#) might change over time as a result. Such credentials either have the "Backup Eligibility" flag set or the authenticator metadata statement has [multiDeviceCredentialSupport](#) set to "implicit".

### **attestationCertificateKeyIdentifiers, of type [DOMString\[\]](#)**

A list of the attestation certificate public key identifiers encoded as hex string.

This value MUST be calculated according to method 1 for computing the keyIdentifier as defined in [RFC5280](#) section 4.2.1.2. The hex string MUST NOT contain any non-hex characters (e.g. spaces). All hex letters MUST be lower case. This field MUST be set if neither aaid nor aaguid are set. Setting this field implies that the attestation certificate(s) are dedicated to a single authenticator model.

All [attestationCertificateKeyIdentifier](#) values should be unique within the scope of the Metadata Service.

Note: FIDO U2F Authenticators typically do not support AAID nor AAGUID, but they use attestation certificates dedicated to a single authenticator model.

### **friendlyNames, of type [FriendlyNames](#)**

A human-readable friendly name of the authenticator / passkey provider in multiple languages. The name is intended to be shown to end users. A name in English language ("en-US") is mandatory, localized names for other languages are optional.

### **description, of type [DOMString](#)**

A human-readable, short description of the authenticator, in English.

Note: This description should help an administrator configuring authenticator policies. This description might deviate from the description returned by the ASM for that authenticator.

This [description](#) should contain the public authenticator trade name and the publicly known vendor name.

This [description](#) MUST be in English, and only contain ASCII [ECMA-262](#) characters.

This [description](#) SHALL NOT exceed a maximum length of 200 characters.

### **alternativeDescriptions, of type [AlternativeDescriptions](#)**

A list of human-readable short descriptions of the authenticator in different languages.

### **authenticatorVersion, of type [unsigned long](#)**

Earliest (i.e. lowest) trustworthy [authenticatorVersion](#) meeting the requirements specified in this metadata statement.

Adding new StatusReport entries with status UPDATE\_AVAILABLE to the metadata BL0B object [\[FIDOMetadataService\]](#) MUST also change thisauthenticatorVersion if the update fixes severe security issues, e.g. the ones reported by preceding StatusReport entries with status code USER\_VERIFICATION\_BYPASS, ATTESTATION\_KEY\_COMPROMISE, USER\_KEY\_REMOTE\_COMPROMISE, USER\_KEY\_PHYSICAL\_COMPROMISE, REVOKED.

It is RECOMMENDED to assume increased risk if this version is higher (newer) than the firmware version present in an authenticator. For example, if a StatusReport entry with status USER\_VERIFICATION\_BYPASS or USER\_KEY\_REMOTE\_COMPROMISE precedes the UPDATE\_AVAILABLE entry, than any firmware version lower (older) than the one specified in the metadata statement is assumed to be vulnerable.

The specified version should equal the value of the 'firmwareVersion' member of the authenticatorGetInfo response. If present, see [\[FIDOCTAP\]](#).

The firmware version of the authenticator providing the attestation can be found in the attestation certificate in extension id-fido-gen-ce-fw-version (OID 1.3.6.1.4.1.45724.1.1.5).

### **protocolFamily, of type [DOMString](#)**

The FIDO protocol family. The values "uaf", "u2f", and "fido2" are supported.

Metadata Statements for U2F authenticators MUST set the value of [protocolFamily](#) to "u2f". Metadata statement for UAF authenticator MUST set the value of [protocolFamily](#) to "uaf", and FIDO2/WebAuthentication Authenticator implementations MUST set the value of [protocolFamily](#) to "fido2".

### **schema, of type [unsigned short](#)**

The Metadata Schema version

Metadata schema version defines what schema of the metadata statement is currently present. The schema version of this version of the specification is 3.

### **upv, of type [Version\[\]](#)**

The FIDO unified protocol version(s) (related to the specific protocol family) supported by this authenticator. See [\[UAFProtocol\]](#) for the formal definition of the `Version` structure (containing major and minor version numbers).

The unified protocol version is determined as follows:

- in the case of FIDO UAF, use the upv value as specified in the respective "OperationHeader" field, see [\[UAFProtocol\]](#).
- in the case of U2F, use
  - major version 1, minor version 0 for U2F v1.0
  - major version 1, minor version 1 for U2F v1.1
  - major version 1, minor version 2 for U2F v1.2 also known as CTAP1
- in the case of FIDO2/CTAP2, use
  - major version 1, minor version 0 for CTAP 2.0
  - major version 1, minor version 1 for CTAP 2.1
  - major version 1, minor version 2 reserved, CTAP 2.2 was skipped
  - major version 1, minor version 3 for CTAP 2.3

### **authenticationAlgorithms, of type [DOMString\[\]](#)**

The list of authentication algorithms supported by the authenticator.

Must be set to the *complete list* of the supported ALG\_ constant case-sensitive string names defined in the FIDO Registry of Predefined Values [\[FIDORRegistry\]](#) (section "Authentication Algorithms") if the authenticator supports multiple algorithms. E.g. "secp256r1\_ecdsa\_sha256\_raw", "secp256r1\_ecdsa\_sha256\_der".

The list MUST NOT be empty.

#### **FIDO UAF Authenticators**

For verification purposes, the fieldSignatureAlgAndEncoding in the FIDO UAF authentication assertion [\[UAFAuthnCommands\]](#) should be used to determine the actual signature algorithm and encoding.

#### **FIDO U2F Authenticators**

FIDO U2F only supports one signature algorithm and encoding:

ALG\_SIGN\_SECP256R1\_ECDSA\_SHA256\_RAW [\[FIDORRegistry\]](#).

### **publicKeyAlgAndEncodings, of type [DOMString](#)[]**

The list of public key formats supported by the authenticator during registration operations.

Must be set to the *complete list* of the supported ALG\_KEY constant case-sensitive string names defined in the FIDO Registry of Predefined Values [\[FIDORRegistry\]](#) if the authenticator model supports multiple encodings. See section "Public Key Representation Formats", e.g. "ecc\_x962\_raw", "ecc\_x962\_der".

Because this information is not present in APIs related to authenticator discovery or policy, a FIDO server MUST be prepared to accept and process any and all key representations defined for any public key algorithm it supports. The list MUST NOT be empty. If there are multiple values they MUST be ordered by preference.

#### **FIDO UAF Authenticators**

For verification purposes, the fieldPublicKeyAlgAndEncoding in the FIDO UAF registration assertion [\[UAFAuthnCommands\]](#) should be used to determine the actual encoding of the public key.

#### **FIDO U2F Authenticators**

FIDO U2F only supports one public key encoding:ALG\_KEY\_ECC\_X962\_RAW [\[FIDORRegistry\]](#).

### **attestationTypes, of type [DOMString](#)[]**

Must be set to the *complete list* of the supported ATTESTATION\_ constant case-sensitive string names. See section "Authenticator Attestation Types" of FIDO Registry [\[FIDORRegistry\]](#) for all available attestation formats, e.g. "basic\_full".

### **userVerificationDetails, of type [VerificationMethodANDCombinations](#)[]**

A list of *alternative* VerificationMethodANDCombinations.

userVerificationDetails is a two dimensional array, that informs RP what VerificationMethodANDCombinations user may be required to perform in order to pass user verification, e.g User need to pass fingerprint, or faceprint, or password and palm print, etc.

If this entry is missing, any user verification method could be implemented - including "none", "presence\_internal" and other methods - including methods not formally defined in the FIDO Registry [\[FIDORRegistry\]](#). Depending on the "protocolFamily", the authentication assertion might contain further details.

Consider this userVerificationDetails example:

```
[
  [
    { "userVerificationMethod": "fingerprint_internal" }
  ],
  // OR
  [
    { "userVerificationMethod": "passcode_internal" }
  ],
  // OR
  [
    { "userVerificationMethod": "faceprint_internal" },
    // AND
    { "userVerificationMethod": "voiceprint_internal" }
  ]
]
```

In this example we have user verification details that describe these potential scenarios: User has an authenticator model that requires

1. Fingerprint, or
2. Passcode, or
3. Faceprint and Voiceprint - where Voiceprint and Faceprint must be provided in order to pass user verification.

The RP verifying attestation or assertion, by checking UV flag in the response knows that one of the user verification combinations been passed.

Note: FIDO2 "Security Keys" will typically support "none", or "presence\_internal", or "passcode\_external" [\[FIDOCTAP\]](#), i.e.

```
[
  [
    { "userVerificationMethod": "none" }
  ],
  [
    { "userVerificationMethod": "presence_internal" }
  ],
  [
    { "userVerificationMethod": "passcode_external" }
  ],
  [
    { "userVerificationMethod": "passcode_external" },
    { "userVerificationMethod": "presence_internal" }
  ]
]
```

The FIDO Client will typically prevent "none" (silent authentication) and "passcode\_external" (without "presence\_internal") from being used in practice, see [\[WebAuthn\]](#).

#### **keyProtection, of type [DOMString\[\]](#)**

The list of key protection types supported by the authenticator. Must be set to the *complete list* of the supported KEY\_PROTECTION\_ constant case-sensitive string names defined in the FIDO Registry of Predefined Values [\[FIDORRegistry\]](#) in section "Key Protection Types" e.g. "secure\_element". Each value MUST NOT be empty.

Note: The keyProtection specified here denotes the effective security of the attestation key and Uauth private key and the effective trustworthiness of the attested attributes in the "sign assertion". Effective security means that key extraction or injecting malicious attested attributes is only possible if the specified protection method is compromised. For example, if keyProtection=TEE is stated, it shall be impossible to extract the attestation key or the Uauth private key or to inject any malicious attested attributes *without breaking the TEE*.

#### **isKeyRestricted, of type [boolean](#)**

This entry is set to true, if the Uauth private key is restricted by the *authenticator* to only sign valid FIDO signature assertions. This entry is set to false, if the authenticator doesn't restrict the Uauth key to only sign valid FIDO signature assertions. In this case, the calling application could potentially get any hash value signed by the authenticator. If this field is missing, the assumed value is isKeyRestricted=true.

Note: Only in the case of isKeyRestricted=true, the FIDO server can trust a signature counter, transaction text, or any other extension in the signature assertion to have been correctly processed/controlled by the authenticator.

#### **isFreshUserVerificationRequired, of type [boolean](#)**

This entry is set to true, if Uauth key usage *always* requires a fresh user verification. If this field is missing, the assumed value is isFreshUserVerificationRequired=true. This entry is set to false, if the Uauth key can be used without requiring a fresh user verification, e.g. without any additional user interaction, if the user was verified a (potentially configurable) caching time ago.

In the case of isFreshUserVerificationRequired=false, the FIDO server MUST verify the registration response and/or authentication response and verify that the (maximum) caching time (sometimes also called "authTimeout") is acceptable.

This entry solely refers to the user verification. In the case of transaction confirmation, the authenticator MUST always ask the user to authorize the specific transaction.

Note that in the case of isFreshUserVerificationRequired=false, the calling App could trigger use of the key without user involvement. In this case it is the responsibility of the App to ask for user consent.

#### **matcherProtection, of type [DOMString\[\]](#)**

The list of matcher protections supported by the authenticator. Must be set to the *complete list* of the supported MATCHER\_PROTECTION constant case-sensitive string names defined in the FIDO Registry of Predefined Values [\[FIDORRegistry\]](#). See section "Matcher Protection Types", e.g. "on\_chip". This value MUST NOT be empty.

If multiple user verification methods are supported, either (a) one entry per method or the minimum security level over all methods could be specified.

If multiple alternative implementations exist, then each entry must reflect the *weakest* implementation of all alternative implementations.

If a user verification method implementation is split across multiple components, then this value must reflect the *weakest* implementation of all those components.

The matcherProtection specified here denotes the effective security of the FIDO authenticator's user verification. This means that a false positive user verification implies breach of the stated method. For example, if matcherProtection=TEE is stated, it shall be impossible to trigger use of the Uauth private key when bypassing the user verification *without breaking the TEE*.

#### **cryptoStrength, of type [unsigned short](#)**

The authenticator's **overall claimed cryptographic strength** in bits (sometimes also called security strength or security level). If this value is absent, the cryptographic strength is unknown. If the cryptographic strength of one of the involved cryptographic methods is unknown the overall claimed cryptographic strength is also unknown.

See [\[FIDOAuthenticatorSecurityRequirements\]](#), requirement 2.1.4, "Overall Claimed Cryptographic Strength"

#### **attachmentHint, of type [DOMString\[\]](#)**

The list of supported attachment hints describing the method(s) by which the authenticator communicates with the FIDO user device. Must be set to the *complete list* of the supported ATTACHMENT\_HINT constant case-sensitive string names defined in the FIDO Registry of Predefined Values [\[FIDOREgistry\]](#). See section "Authenticator Attachment Hints", e.g. "nfc".

This value MUST be present for all authenticators supporting CTAP 2.2 or newer. This value SHOULD be present for all authenticators supporting CTAP 2.1. If the value is provided, the array MUST NOT be empty.

Note: The connection state and topology of an authenticator may be transient and cannot be relied on as authoritative by a relying party, but the metadata field should have all the bit flags set for the topologies possible for the authenticator. For example, an authenticator instantiated as a single-purpose hardware token that can communicate over bluetooth should set ATTACHMENT\_HINT\_EXTERNAL but not ATTACHMENT\_HINT\_INTERNAL.

For FIDO2 the values of attachmentHint MUST correspond to the authenticator.getInfo.transports if present.

See the field authenticatorGetInfo for FIDO2 authenticators; which expose similar information in the 'transports' member when invoking the 'authenticatorGetInfo' method. See [\[FIDOC2TAP\]](#)

#### **tcDisplay, of type [DOMString\[\]](#)**

The list of supported transaction confirmation display capabilities. Must be set to include a valid combination, as specified in FIDO Registry of Predefined Values [\[FIDOREgistry\]](#) section "Transaction Confirmation Display Types", of the supported TRANSACTION\_CONFIRMATION\_DISPLAY constant case-sensitive string names e.g. "any", "hardware".

This value MUST be empty, if transaction confirmation is not supported by the authenticator.

The tcDisplay specified here denotes the effective security of the authenticator's transaction confirmation display. This means that only a breach of the stated method allows an attacker to inject transaction text to be included in the signature assertion which hasn't been displayed and confirmed by the user.

#### **tcDisplayContentType, of type [DOMString](#)**

Supported MIME content type [\[RFC2049\]](#) for the transaction confirmation display, such as text/plain or image/png.

This value MUST be present if transaction confirmation is supported, i.e. tcDisplay is non-zero.

#### **tcDisplayPNGCharacteristics, of type [DisplayPNGCharacteristicsDescriptor\[\]](#)**

A list of *alternative* DisplayPNGCharacteristicsDescriptor.

Each of these entries is one alternative of supported image characteristics for displaying a PNG image.

This list MUST be present if PNG-image based transaction confirmation is supported, i.e. tcDisplay is non-zero and tcDisplayContentType is image/png.

#### **attestationRootCertificates, of type [DOMString\[\]](#)**

List of attestation trust anchors for the batch chain in the authenticator attestation. Each element of this array represents a PKIX [\[RFC5280\]](#) X.509 certificate that is a valid trust anchor for this authenticator model. Multiple certificates might be used for different batches of the same model. The array does not represent a certificate chain, but only the trust anchor of that chain. A trust anchor can be a root certificate, an intermediate CA certificate or even the attestation certificate itself.

Each array element is a base64-encoded (section 4 of [\[RFC4648\]](#)), DER-encoded [\[ITU-X690-2008\]](#) PKIX certificate value. Each element MUST be dedicated for authenticator attestation.

Note: A certificate listed here is a trust anchor. It might (1) be the actual certificate presented by the authenticator, or it might (2) be an issuing authority certificate from the vendor that the attestation certificate chains to. In the case of (1), a binary comparison is sufficient to determine if the attestation trust anchor is the attestation certificate itself.

In the case of "uaf" protocol family, the attestation certificate itself and the ordered certificate chain are included in the registration assertion (see [\[UAFAuthnCommands\]](#)).

Either

1. the manufacturer attestation trust anchor or
2. the trust anchor dedicated to a specific authenticator model

MUST be specified.

In the case (1), the trust anchor certificate might cover multiple authenticator models. In this case, it must be possible to uniquely derive the authenticator model from the Attestation Certificate. When using AAID or AAGUID, this can be achieved by either specifying the AAID or AAGUID in the attestation certificate using the extension id-fido-gen-ce-aaaid { 1 3 6 1 4 1 45724 1 1 1 } or id-fido-gen-ce-aaguid { 1 3 6 1 4 1 45724 1 1 4 } or - when neither AAID nor AAGUID are defined - by using the attestationCertificateKeyIdentifier method.

In the case (2) this is not required as the trust anchor only covers a single authenticator model.

When supporting surrogate basic attestation only (see [\[UAFProtocol\]](#), section "Surrogate Basic Attestation"), no attestation trust anchor is required/used. So this array MUST be empty in that case.

#### **ecdaaTrustAnchors, of type [EcdaaTrustAnchor\[\]](#)**

A list of trust anchors used for ECDAA attestation. This entry MUST be present if and only if attestationType includes ATTESTATION\_ECDAA. The entries in attestationRootCertificates have no relevance for ECDAA attestation. Each ecdaaTrustAnchor MUST be dedicated to a single authenticator model (e.g. as identified by its AAID/AAGUID).

Note: This field only applies to UAF authenticators.

#### **icon, of type [DOMString](#)**

A data: url [\[RFC2397\]](#) encoded [\[PNG\]](#) or [\[SVG11\]](#) (light mode) icon for the Authenticator (e.g., depicting the security key). This icon is intended to be shown to users by RPs. Use of [\[SVG11\]](#) format is mandatory if any of the iconDark, providerLogoLight and/or providerLogoDark is used in addition to icon. Use of [\[SVG11\]](#) is recommended if only icon is used. The icon is more specific than the provider logo and should be shown if present.

#### **iconDark, of type [DOMString](#)**

A data: url [\[RFC2397\]](#) encoded [\[SVG11\]](#) dark mode icon for the Authenticator (e.g., depicting the security key). This icon is intended to be shown to users by RPs. The icon is more specific than the provider logo and should be shown if present.

#### **providerLogoLight, of type [DOMString](#)**

A data: url [\[RFC2397\]](#) encoded [\[SVG11\]](#) light mode icon for the provider (e.g., logomark of the passkey provider). The SVG MUST meet all of the requirements defined in [§ 4.1 SVG requirements](#). This icon is intended to be shown to users by RPs.

#### **providerLogoDark, of type [DOMString](#)**

A data: url [\[RFC2397\]](#) encoded [\[SVG11\]](#) dark mode icon for the provider (e.g., logomark of the passkey provider). The SVG MUST meet all of the requirements defined in [§ 4.1 SVG requirements](#). This icon is intended to be shown to users by RPs.

#### **supportedExtensions, of type [ExtensionDescriptor\[\]](#)**

List of extensions supported by the FIDO UAF authenticator. This field only applies to UAF authenticators.

For FIDO2 authenticators see `authenticatorGetInfo`

#### **multiDeviceCredentialSupport, of type [DOMString](#)**

When set to "unsupported" it means that all private keys relating to the [Public Key Credential Source \[WebAuthn\]](#) are designed to stay within the authenticator boundary. Consequently, the security characteristics of this Metadata Statement apply to *all* keys.

When set to "explicit" it means that the authenticator explicitly marks keys as either multi-device keys or single-device keys via the "Backup Eligibility" flag [\[WebAuthn\]](#).

When set to "implicit" it means that all private keys relating to [Public Key Credential Source \[WebAuthn\]](#) may be backed up.

The field [authenticatorGetInfo / supportedExtensions](#) will include the "supplementalPubKeys" extension if the authenticator supports it in general.

If this [multiDeviceCredentialSupport](#) field is missing the implicit value is "unsupported" (to provide backwards compatibility).

#### **authenticatorGetInfo, of type [AuthenticatorGetInfo](#)**

Describes supported versions, extensions, AAGUID of the device and its capabilities.

The information is the same reported by an authenticator when invoking the 'authenticatorGetInfo' method, see [\[FIDOCTAP\]](#).

Note: This field MUST be present for FIDO2 authenticators that *natively* support FIDO CTAP [\[FIDOCTAP\]](#), i.e., when protocolFamily is "fido2".

Authenticators only implementing platform APIs shall not provide the field `authenticatorGetInfo`.

FIDO UAF and FIDO U2F authenticators do not support `authenticatorGetInfo`.

The FIDO Alliance does not verify the certification status information in field certifications of the `authenticatorGetInfo` response [\[FIDOCTAP\]](#).

Authoritative information on the authenticator certification status is included in the `StatusReport` field of the respective Metadata entry [\[FIDOMetadataService\]](#).

#### **cxConfigURL, of type [DOMString](#)**

Specifies the URL for retrieving the configuration details for credential exchange (CX).

When exchanging credentials, the passkey provider to export the credential might retrieve the credential exchange configuration details for the the importing provider in order to provide additional security. More details can be found in Credential Exchange Protocol specification that can be found on the FIDO [Credential Exchange Specifications](#) web page.

## 4.1. SVG requirements

*This section is normative.*

All [\[SVG11\]](#) provider icons MUST adhere to the SVG Portable/Secure (SVG-P/S) profile defined in <https://datatracker.ietf.org/doc/draft-svg-tiny-ps-abrotman/09/>.

Additional requirements:

1. Format: SVG Version: 1.2 with baseProfile as "tiny-ps"
2. Elements: vector-based (cannot contain raster components)
3. Dimensions: square aspect ratio
4. The `<title>` element MUST be populated with the English version of the provider friendly name
5. The SVG MUST not contain comments or extra text

## 5. Metadata Statement Format

*This section is not normative.*

A FIDO Authenticator Metadata Statement is a document containing a JSON encoded [dictionary](#) [MetadataStatement](#).

### 5.1. UAF Example

Example of the metadata statement for an UAF authenticator with:

- authenticatorVersion 2.
- Fingerprint based user verification allowing up to 5 registered fingers, with false acceptance rate of 0.002% and rate limiting attempts for 30 seconds after 5 false trials.
- Authenticator is embedded with the FIDO User device.
- The authentication keys are protected by TEE and are restricted to sign valid FIDO sign assertions only.
- The (fingerprint) matcher is implemented in TEE.
- The Transaction Confirmation Display is implemented in a TEE.
- The Transaction Confirmation Display supports display of "image/png" objects only.
- Display has a width of 320 and a height of 480 pixel. A bit depth of 16 bits per pixel offering True Color (=Color Type 2). The zlib compression method (0). It doesn't support filtering (i.e. filter type of=0) and no interlacing support (interlace method=0).
- It uses the ALG\_SIGN\_SECP256R1\_ECDSA\_SHA256\_RAW authentication algorithm.
- It uses the ALG\_KEY\_ECC\_X962\_RAW public key format (0x100=256 decimal).
- It only implements the ATTESTATION\_BASIC\_FULL method (0x3E07=15879 decimal).
- It implements UAF protocol version (upv) 1.0 and 1.1.

#### EXAMPLE 1

```
{  
  "legalHeader": "https://fidoalliance.org/metadata/metadata-statement-legal-header/",  
  "friendlyNames": {"en-US": "FIDO UAF Sample"},  
  "description": "FIDO Alliance Sample UAF Authenticator",  
  "aaid": "1234#5678",  
  "alternativeDescriptions": {  
    "ru-RU": "Пример UAF аутентификатора от FIDO Alliance",  
    "fr-FR": "Exemple UAF authenticator de FIDO Alliance"  
  },  
  "authenticatorVersion": 2,  
  "protocolFamily": "uaf",  
  "schema": 3,  
  "upv": [  
    { "major": 1, "minor": 0 },  
    { "major": 1, "minor": 1 }  
  ],  
  "authenticationAlgorithms": ["secp256r1_ecdsa_sha256_raw"],  
  "publicKeyAlgAndEncodings": ["ecc_x962_raw"],  
  "attestationTypes": ["basic_full"],  
  "userVerificationDetails": [  
    {  
      "userVerificationMethod": "fingerprint_internal",  
      "baDesc": {  
        "selfAttestedFAR": 0.00002,  
        "maxRetries": 5,  
        "blockSlowdown": 30,  
        "maxTemplates": 5  
      }  
    }  
  ]  
}
```

```
        },
        "keyProtection": ["hardware", "tee"],
        "isKeyRestricted": true,
        "matcherProtection": ["tee"],
        "cryptoStrength": 128,
        "attachmentHint": ["internal"],
        "tcDisplay": ["any", "tee"],
        "tcDisplayContentType": "image/png",
        "tcDisplayPNGCharacteristics": [
            {
                "width": 320,
                "height": 480,
                "bitDepth": 16,
                "colorType": 2,
                "compression": 0,
                "filter": 0,
                "interlace": 0
            }
        ],
        "attestationRootCertificates": [
            "MIICPTCAe0gAwIBAgIJA0uexvU30y2wMAoGCCqGSM49BAMCMHsxDAAeBgNVBAMM
F1NhbxBsZSBBdHRLc3RhdGvbIBSb290MRYwFAYDVQQKDA1GSURPIEsbGhbmn1
MREwDwYDVQQLDahVQUYgVFdHLDESMBAGA1UEBwwJUGFsbyBBbHRvMQswCQYDVQQI
DAJDQTELMAkGA1UEBhMCVVMwHhcNMTQwNjE4MTMzMzMyWhcNNDExMTAzMTMzMzMy
WjB7MSAwHgYDVQQDDBdTYW1wbGUgQXR0ZXN0YXRpb24gUm9vdDEwMBQGA1UECgwN
RkLETyBBbGxpYW5jZTERMA8GA1UECwwIVUFGIFRXRywxEjAQBgNVBACMCVBhbG8g
QWx0bzELMAkGA1UECAwCQ0ExCzAJBgNVBAYTA1VTMFkwEwYHKoZIzj0CAQYIKoZI
zj0DAQcDQgAEH8hv2D0HXa59/BmpQ7RZehL/FMGzFd1QBg9vAuP0Z3ajnuQ94PR7
aMzH33nUSBr8fHYDrq0Bb58pxGqHJRY/X/6NQME4wHQYDVR0OBBYEFPoHA3CLhxFb
C0It7zE4w8hk5EJ/MB8GA1UDiWQYMBaAFPoHA3CLhxFbC0It7zE4w8hk5EJ/MAwG
A1UdEwQFQFMAMBAf8wCgYIKoZIzj0EAwIDSAAwRQIhAJ06QSXt9ihIbEKYKIjsPkri
VdLIgtfsbDSu7ErJfzr4AiBqoYCF0+zI55aQeAHjIzA9Xm63rruAxBZ9ps9z2XN
lQ=="
        ],
        "icon": "data:image/png;base64,
iVBORw0KGgoAAAANSUhEUgAAAE8AAAAvCAYAAACiwJfcAAAAAXNSR0IArs4c6QAAAARnQU1BAACx
jwv8YQUAAAjCehZcwAADsMAAA7DAcdvqGQAAAahSURBVGhD7Zr5bxR1GMf9KzTB8AM/YEhE2W7p
QZcWKKBclSpHATLelARE7kNECCA3FkWK0CKKSCFIsKBcgVCDWGNEsDAYidwgggJBiRiMhFc/4wy8
884zu9NdlnGTfZJP2n3n0++88933fveBBx+PqCzJkTUvBbLmpUDWvBTImpcCSzvXLCdX9R05Sk19
bb5atf599fG+/erA541q47aP1LLVa9SiYvNUi8Ii8d5kGTsi30NFv7ai9n7QZPMwbdys2erU2Xmq
Udy8+ZcaNmGimE8yXN3RUD3a18nF0fUlovZ+0CTzWpd2Vj+e0m1bEyy6Dx4i5pUMGwveo506q227
dtuWBIuffr6oWpV0FPNLhow1751Nm21LrPH3rVtWjfz66Lfql8tX7FR19YFSXsmSseb9ce0GbYk7
MNUcGPg8ZsbMe9rfQaaaV/JMX9sqdzDCSvp0kZHM7Zg9x/bLHcMnThb16eJ+mVfQq8yaUZQNG64i
XZ+0/kq6u0ZF00QtatdWkfXnRQ99Bj91R50IFnk54jN0mkUiql03XDw+Ml+98mKB6tW7rWpZcPc+
0zg4tLrYlUc86E6eGdjIMubVpcusearfgyIGRk6brhZVr/JcHzooL7550jedLExopWcApi2ZUqhu
7JLvrVsQU81zkz0PeemMRYvVuQsX7PbiDQY5JvZonftK+1VY8H9utx530h0ob+jmRYqj6ouaYvEe
nW/WlYjp8cwbMm682tPwqW1R4tj/2SH13IRJYl4moZvXpiSqd7dXtQHxa/PK3/+BWsk1dTgHu6V
8tQJ3bwFkwpFrU0Q50s1r3levm8zZcq17+BBaw7K81EK5qzkYear9A8p7P3GzDK+nd3DQow+6UC
8SVN82iuV38im7NtaXtV1CVq6Rgw4pkmsbdi3bu2De7YfaBBxcqfvqPrUjFQNTQ221fdUVVT68rT
JKF5DnSmUjgdqg4mSS9pmsfDJR3G6ToH0iW9aV7LWLHYXK1lTDt0LTAtkYIaamp1QjVv++uyGUxV
dJ0DNVXSm+b1qRxpl84ddfX1Lp10/d69tsod0vs5hGre9xu8o+fpLR1cGhNTD6Z57C9KMWXefJd0
Z94bb90qd1R0nS7qITTzHimMqivb03g0DdVyk3WQBhBztK35YKNd0nc803acS6fDZFgKaXLsEJp5
rdrlibqp89cJcs/m7Tvs0rkjGfn4b0kPoZn3UJuI0rnZ22yP1fmvUx+05gSqeBV1m+zSuYNVhq7T
WbdilVlvjplLlop6CLXP+2qtvGLIL/1vimISdMBgzSoFZyu6Tqd+jzxgsPaV9BCqee/NjYk6v61K
9cwiUc/STtf1HDpM3b592y7h3Thx50zK69HLPYWuAwaqS5cv26q7ceb8efVYaReP3iFU8zj1knSw
ZXHMmnCjY00galo7UQfSCM3qQr2H/XFP7ssXx45Yl91ByeCep4mozoH+1fG3xD4tT7x8kwyj8nw
b9ev26V0B6d+7H4zKvudAH537Fjqy0HdJnHEuzmXq/Wjx0bvNmbv7nhysX2aVsWtC8+48aLeap
E7p5wKZi0A2AQRV5nvR4E+uJc+b61kApqInxBgmd/4V5QP/mt18HDC7sRHftmeu5lmhV0rn/ALX2
32bqd4BFnDx7Vi1cWS2uff0IbB47qexxmUj9QutYjupd3tYD6abWBBMrh+apNb0KrNF1+ugCa4ri
XGfwMPPtViavhU3YMOAAnuUb/R07L0y0Se0adE88ApsXFGff30ynhlJgm51CU6vN9EzgnpvHBFUy
iVraePiwJ53DF5ZTznomENg85kNUd2oJi2Wpr40mmkfN4x4zHfiVFc8Dv8NzuhNq0idilGvA6DGu
eZw078AAQn6ciEk6+rw5CvjqvNDYPOoIuwaKShrxAuXLlkH4aYuGfMYDc10WF5Ta31hPJ0fcUhr
U/J1INi6c6elRYdBpo6++Yfjx61lGNfRm4MD5rJ1j3FoGhnjDSBNarYugMLyMszKpb7tXpoHfpS8
h3Wn117NFNk54Xx1wDGIImYzXYefh6z/cKtVm4FRx9a9V0Gn7Yr31riIMRiHFkk7zaFKY0A2hG0II1
22/34
```

```

    "userVerificationMethods": [
        {
            "userVerificationMethod": "fingerprint_internal",
            "baDesc": {
                "selfAttestedFAR": 0.000002,
                "maxTemplates": 5,
                "maxRetries": 5,
                "blockSlowdown": 0
            }
        },
        {
            "userVerificationMethod": "passcode_internal",
            "caDesc": {
                "base": 10,
                "minLength": 4
            }
        }
    ]
}

```

Example of an *User Verification Methods* entry for an authenticator with:

- Fingerprint based user verification method, with:
  - the ability for the user to enroll up to 5 fingers (reference data sets) with
    - a false acceptance rate of 1 in 50000 (0.002%) per finger. This results in a FAR of 0.01% (0.0001).
    - The fingerprint verification will be blocked after 5 unsuccessful attempts.
- A PIN code with a minimum length of 4 decimal digits has to be set-up as alternative verification method. Entering the PIN into the authenticator will be required to re-activate fingerprint based user verification after it has been blocked.

#### EXAMPLE 2

```

[

    [
        {
            "userVerificationMethod": "fingerprint_internal",
            "baDesc": {
                "selfAttestedFAR": 0.000002,
                "maxTemplates": 5,
                "maxRetries": 5,
                "blockSlowdown": 0
            }
        }
    ],
    [
        {
            "userVerificationMethod": "passcode_internal",
            "caDesc": {
                "base": 10,
                "minLength": 4
            }
        }
    ]
]

```

## 5.2. U2F Example

Example of the metadata statement for an U2F authenticator with:

- authenticatorVersion 2.
- Touch based user presence check.
- Authenticator is a USB pluggable hardware token.
- The authentication keys are protected by a secure element.
- The user presence check is implemented in the chip. From the perspective of the authenticator, the presence check is optional for U2F\_AUTHENTICATE.
- The Authenticator is a pure second factor authenticator.
- It uses the ALG\_SIGN\_SECP256R1\_ECDSA\_SHA256\_RAW authentication algorithm.
- It uses the ALG\_KEY\_ECC\_X962\_RAW public key format.

- It only implements the ATTESTATION\_BASIC\_FULL method.
- It implements U2F protocol versions 1.2, 1.1 and 1.0

### EXAMPLE 3

```
{
  "legalHeader": "https://fidoalliance.org/metadata/metadata-statement-legal-header/",
  "friendlyNames": {"en-US": "FIDO U2F Sample"},
  "description": "FIDO Alliance Sample U2F Authenticator",
  "alternativeDescriptions": {
    "ru-RU": "Пример U2F аутентификатора от FIDO Alliance",
    "fr-FR": "Exemple U2F authenticator de FIDO Alliance",
    "zh-CN": "FIDO Alliance U2F 样例"
  },
  "attestationCertificateKeyIdentifiers": ["7c0903708b87115b0b422def3138c3c864e44573"],
  "protocolFamily": "u2f",
  "schema": 3,
  "authenticatorVersion": 2,
  "upv": [
    { "major": 1, "minor": 0 },
    { "major": 1, "minor": 1 },
    { "major": 1, "minor": 2 }
  ],
  "authenticationAlgorithms": ["secp256r1_ecdsa_sha256_raw"],
  "publicKeyAlgAndEncodings": ["ecc_x962_raw"],
  "attestationTypes": ["basic_full"],
  "userVerificationDetails": [
    [
      {"userVerificationMethod": "none"}
    ],
    [
      {"userVerificationMethod": "presence_internal"}
    ]
  ],
  "keyProtection": ["hardware", "secure_element"],
  "matcherProtection": ["on_chip"],
  "cryptoStrength": 128,
  "attachmentHint": ["external", "wired", "nfc"],
  "tcDisplay": [],
  "attestationRootCertificates": [
    "MIICPTCC Ae0gAwIBAgIJA0uexvU30y2wMAoGCCqGSM49BAMCMHsxDIAeBgNVBAMM
    F1NhBxBsZSBBdHRlc3RhdGlvbIBSb290MRYwFAYDVQQKDA1GSURPIEFSbGlhbhNL
    MREwDwYDVQQLDAhVQUYgVFdHLDfBAGA1UEBwwJUGFsbyBBbHRvMQswCQYDVQQI
    DAJDQTELMAkGA1UEBhMCVVMwHhcNMTQwNjE4MTMzMzMyWhcNNDExMTAzMTMzMzMy
    WjB7MSAwHgYDVQQDDBdTYW1wbGUgQXR0ZXN0YXRpb24gUm9vdDEwMBQGA1UECgwN
    Rk1ETyBBbGxpYW5jZTERMA8GA1UECwwIVUFGIFRXRywxEjAQBgNVBAcMCVBhbG8g
    QWx0bzELMAkGA1UECAwCQ0ExCzAJBgNVBAYTAlVTMfkwEwYHKoZIzj0CAQYIKoZI
    zj0DAQcDQgAEH8hv2D0HXa59/BmpQ7RZehL/FMGzFd1QBg9vAUp0Z3ajnuQ94PR7
    aMzH33nUsBr8fHYDrq0Bb58pxGqHJRYX/6NQME4wHQYDVR00BBYEFPoHA3CLhxFb
    C0It7zE4w8hk5EJ/MB8GA1UdIwQYMBaAFPoHA3CLhxFbC0It7zE4w8hk5EJ/MAwG
    A1UdEwQFMAMBAf8wCgYIKoZIzj0EAwIDSAAwRQIhAJ06QSXt9ihIbEKYKIjsPkri
    VdLIgtfsbDSu7ErJfzr4AiBqoYCZf0+zI55aQeAHjIzA9Xm63rruAxBZ9ps9z2XN
    lQ=="
  ],
  "icon": "data:image/png;base64,
    iVBORw0KGgoAAAANSUhEUgAAAE8AAAAvCAYAACiwJfcAAAAAXNSR0IArs4c6QAAAARnQU1BAACx
    jwv8YQUAAAjCehZcwAADsMAAA7DAcdvqGQAAAhSURBVGhD7Zr5bxR1GMf9KzTB8AM/YEhE2W7p
    QZcWKKBclSpHATLELARE7kNECCA3FkWK0CKKSCFIkBcgVCDWGNESdAYidwgggJBiRiMhFc/4wy8
    884zu9NdlnGTfZJP2n3n0++88933fveBBx+PqCzJkTUvBbLmpUDWvBTImpcCSZvXLCdX9R05Sk19
    bb5atf599fG+/erA541q47aP1LLVa9SiYVNUi8Ii8d5kGTsi30NFv7ai9n7QZPMwbdys2erU2Xmq
    Udy8+ZcaNmGimE8yXN3RUd3a18nF0fUlovZ+0CTzWpd2Vj+e0m1bEyy6Dx4i5pUMGWveo506q227
    dtuWBIuffr6oWpV0FPNLhow1751Nm21LvtPH3rVtWjfz66Lfql8tX7FRl9YFSXsmSseb9ce0GbYk7
    MNUcGPg8ZsbMe9rfQuaaV/JMX9sqdzDCSvp0kZhmTZg9x7bLHcMnThb16eJ+mVfQq8yaUZQNG64i
  "
}
```

```

XZ+0/kq6u0ZF00QtatdWkfXnRQ99Bj91R50IFnk54jN0mkUiql03XDw+Ml+98mKB6tW7rWpZcPc+
0zg4tLrYlUc86E6eGDjIMubVpcusearfjYGRk6brhZVr/JchzooL7550jedLExopWcApi2ZUqhu
7JLvrVsQU81zkz0PeemMRVvUoQsX7PbiDQY5jVzonftK+1VY8H9utx530h0ob+jmRYqj6ouaYvEe
nW/WlYjp8cwbMm682tPwqW1R4tj/2SH13IRJYl4moZvXpiSqDr7dXtQHxa/PK3/+BWsK1dTgHu6V
8tQJ3bwFkwpFrU0Q50s1r3levm8zCq17+BBaw7K8LEK5qzKYeark9A8p7P3GzDK+nd3DQow+6UC
8SVN82iuv38im7NtaXtV1Cvq6Rgw4pksmbdi3bu2De7YfaBBxcqfvqPrUjFQNTQ221fdUVVT68rT
JKF5DnSmUjgdqg4mSS9pmsfDJR3G6ToH0iW9aV7LWLHYXK1lTDt0LTAtkYIaamp1QjVv++uyGUxV
dJ0DNVXSm+b1qRxpl84ddfX1Lp10/d69tsod0vs5hGre9xu8o+fpLR1cGhNTD6Z57C9KMWXefJd0
Z94bb9oqd1R0nS7qITTzHimMqivb03g0DdVyk3WQBhBztK35YKnd0nc803acS6fDZFgKaXLsEJp5
rdrlibqp89cJcs/m7Tvs0rkjGfN4b0kPoZn3UJuI0rnZ22yP1fmvUx+05gSqeBv1m+zSuYNVhq7T
WbDiLVvljplLlop6CLXP+2qtvGLIL/1vimsdMBgzSoFZyu6Tqd+jzxgsPaV9BCqee/NjYk6v6lK
9cwiUc/STtf1HDpM3b592y7h3Thx5ozK69HLpYwuAwaqS5cv26q7ceb8efVYaReP3iFU8zj1knSw
ZXHMmnCjY00gal07UQfSCM3qQqr2H/XFP7ssXx45Yl91ByeCep4mozoH+1fG3xD4tT7x8kwyj8nw
b9ev26V0B6d+7H4zKvudAH537Fjqyz0HdJnHEuzmXq/Wjx0bvNMbv7nhysX2aVsWtC8+48aLeap
E7p5wKZi0A2AQRV5nvR4E+uJc+b61kApqInxBgm/4V5QP/mt18HDC7sRHftmeu5lmhV0rn/ALX2
32bqd4BFnDx7Vi1cWS2uff0IbB47qexxmUj9QutYjupd3tYD6abWBBMrh+apNb0KrNF1+ugCa4ri
XGfwMPPtViavhU3YM0AAuUb/R07L0y0Se0adE88ApsXFGff30ynhlJgM51CU6vN9EzgnpvHBFUy
iVraePiwJ53DF5ZTznomENg85kNUd2oJi2Wpr40mmkfN4x4zHfiVFc8Dv8NzuhNq0idilGvA6DG
eZw078AAQn6ciEk6+rw5VcvjvqNDYP0oIUwaKShrxAuXL1kH4aYuGfMYDc10WF5Ta31hPJ0fcUhr
U/JlINI6c6elRYdBpo6++Yfjx61lGNfRm4MD5rJ1j3FoGhjDSBNarYUgMLyMsZKpb7tXpoHfPs8
h3Wp1LzNfNk54XxC1wDGUmYzXyefh6z/cKtVm4EBxa9VQGDzYr3LrUMRjHEKkk7zaFKYQA2hGQU1
z+85NFwpxDrkz3vx10GqxQ6BzeNboBk5n8k4nebRh+k1hWfxTF0D1EyWUs5nv+dgQqKaxzuCdE0i
sHl02NQ8ah0mXr12La3m0f9wik9+wLNTMY/86MPo8yiy310fxmT6PWoqG9+DZukYna56mSZt5WWSy
5qVA1rwUyJqXAlnzkiai/gHSD7RkTyihogAAAABJRU5ErkJgg=="
```

}

### 5.3. FIDO2 Example

Example of the metadata statement for an FIDO2 authenticator with:

- AAGUID is set to 0132d110-bf4e-4208-a403-ab4f5f12efe5.
- authenticatorVersion is set to 2.
- Touch based user presence check, and external pin(ClientPin Protocol) support.
- Authenticator is a USB pluggable hardware token with support for NFC.
- The authentication keys are protected by a secure element.
- The user presence check is implemented in the chip. From the perspective of the authenticator, the presence check is optional for getAssertion.
- It uses the ALG\_SIGN\_SECP256R1\_ECDSA\_SHA256\_RAW and ALG\_SIGN\_RSASSA\_PKCSV15\_SHA256\_RAW authentication algorithms.
- It uses the ALG\_KEY\_COSE public key format.
- It only implements the ATTESTATION\_BASIC\_FULL method.
- It implements FIDO2 protocol version 1.0.

#### EXAMPLE 4

```

{
  "legalHeader": "https://fidoalliance.org/metadata/metadata-statement-legal-header/",
  "friendlyNames": {"en-US": "FIDO Sample Security Key"},
  "description": "FIDO Alliance Sample FIDO2 Authenticator",
  "aaguid": "0132d110-bf4e-4208-a403-ab4f5f12efe5",
  "alternativeDescriptions": {
    "ru-RU": "Пример FIDO2 аутентификатора от FIDO Alliance",
    "fr-FR": "Exemple FID02 authenticator de FIDO Alliance",
    "zh-CN": "FIDO Alliance FID02"
  },
  "protocolFamily": "fido2",
  "schema": 3,
}
```

```

"authenticatorVersion": 5,
"upv": [
  { "major": 1, "minor": 0 }
],
"authenticationAlgorithms": ["secp256r1_ecdsa_sha256_raw", "rsassa_pkcs15_sha256_raw"],
"publicKeyAlgAndEncodings": ["cose"],
"attestationTypes": ["basic_full"],
"userVerificationDetails": [
  [
    {"userVerificationMethod": "none"}
  ],
  [
    {"userVerificationMethod": "presence_internal"}
  ],
  [
    {
      "userVerificationMethod": "passcode_external",
      "caDesc": {
        "base": 10,
        "minLength": 4
      }
    },
    {
      "userVerificationMethod": "passcode_external",
      "caDesc": {
        "base": 10,
        "minLength": 4
      },
      {"userVerificationMethod": "presence_internal"}
    }
  ],
  [
    "keyProtection": ["hardware", "secure_element"],
    "matcherProtection": ["on_chip"],
    "cryptoStrength": 128,
    "attachmentHint": ["external", "wired", "wireless", "nfc"],
    "tcDisplay": [],
    "attestationRootCertificates": [
      "MIICPTCC Ae0gAwIBAgIJAQuexvU30y2wMAoGCCqGSM49BAMCMHsxDIAeBgNVBAMM
F1NhBxBsZSBBdHRlc3RhGlvbiBSb290MRYwFAYDVQQKDA1GSURPIEFsbGlhbmNl
MREwDwYDVQQLDahVQUYgVFdHLDESMBAGA1UEBwwJUGFsbyBBbHRvMQswCQYDVQQI
DAJDQTELMAkGA1UEBhMCVVMwHhcNMTQwNjE4MTMzMzMyWhcNNDExMTAzMTMzMzMy
WjB7MSAwHgYDVQQDDBdTYW1wbGUgQXR0ZXRpb24gUm9vdDEWMBQGA1UECgwN
RklETyBBbGxpYW5jZTERMA8GA1UECwwIVUFGIFRXRywxEjAQBgNVBAcMCVBhbG8g
QWx0bzELMAkGA1UECAwCQ0ExCzAJBgNVBAYTA1VTMFkwEwYHKoZIzj0CAQYIKoZI
zj0DAQcDQgAEH8hv2D0HXa59/BmpQ7RZehL/FMGzFd1QBg9vAUoZ3ajnuQ94PR7
aMzH33nUSBr8fHYDrq0Bb58pxGqHJRYX/6NQME4wHQYDVR0OBBYEFPoHA3CLhxFb
C0It7zE4w8hk5EJ/MAwG
A1UdEwQFMAMBAf8wCgYIKoZIzj0EAwIDSAAwRQIhAJ06QSxt9ihIbEKYKIjsPkri
VdLIgtfsbDSu7ErJfzr4AiBqoYCZf0+zI55aQeAHjIzA9Xm63rruAxBZ9ps9z2XN
lQ=="
    ],
    "icon": "data:image/png;base64,
iVBORw0KGgoAAAANSUhEUgAAA8AAAAAvCAYAAACiwJfcAAAAAXNSR0IArs4c6QAAAARnQU1BAACx
jwv8YQUAAAACjEhZcwAADsMAAA7DAcqvGQAAAahSURBVGhD7Zr5bxRlGMf9KzTB8AM/YEhE2W7p
QZcWKKBclSpHATLELARE7kNECCA3FkWk0CKKSCFIIsKBcgVCDWGNESdAYidwgggJBiRiMhFc/4wy8
884zu9NdlnGTfZJP2n3n0++88933fveBBx+PqCzJkTUvBbLmpUDWvBTImpcCSzvXLCdX9R05Sk19
bb5atf599fG+/erA541q47aP1LLVa9SiYvNUi8Ii8d5kGTsi30NFv7ai9n7QZPMwb dys2erU2Xmq
Udy8+ZcaNmGimE8yXN3RUd3a18nF0fUlovZ+0CTzWpd2Vj+e0m1bEyy6Dx4i5pUMGWveo506q227
dtuWBIuffr6oWpV0FPNLhow1751Nm21LvhP3rVtWjfz66Lfql8tX7FRl9YFSXsmSseb9ce0GbYk7
MNUcGPg8ZsbMe9rfQuaaV/JMX9sqdzDCSvp0kZHM TZg9x7bLHcMnThb16eJ+mVfQq8yaUZQNG64i
XZ+0/kq6u0ZF00QtatdWKfXnRQ99Bj91R50IFnk54jN0mkUiql03XDw+Ml+98mKB6tW7rWpZcPc+
0zg4tLrYlUc86E6eGDjIMubVpcusearf gIYGRk6brhZVr/JcHzooL7550jedLExopWcApi2ZUqhu
7JLvrVsQU81zkz0PeemMRYvVuQsX7PbiDQY5JvZonftK+1VY8H9utx530h0ob+jmRYqj6ouaYvEe
nW/WlYjp8cwbMm682tPwqW1R4tj/2SH13IRJYl4moZvXpiSqDr7dXtQHxa/PK3/+BWsK1dTgHu6V
"
  ]
]

```

```

8tQJ3bwFkwFrU0Q50s1r3levm8zZcq17+BBaw7K81EK5qzkYear9A8p7P3GzDK+nd3DQow+6UC
8SVN82iuv38im7NtaXtV1Cvq6Rgw4pkSmbdi3bu2De7YfaBBxcqfvqPrUjFQNTQ221fdUVVT68rT
JKF5DnSmUjgdqg4mSS9pmsfDJR3G6ToH0iW9aV7LWLHYXK11TDt0LTAtkYIaamp1QjVv++uyGUxV
dJ0DNVXSm+b1qRxpl84ddfX1Lp10/d69tsod0vs5hGre9xu8o+fpLR1cGhNTD6Z57C9KMWxefJd0
Z94bb9oqd1R0nS7qITTzHimMqivb03g0DdVyk3WQBhBztK35YKNd0nc803acS6fDZFgKaXLSxEJp5
rdrlIBqp89cJcs/m7Tvs0rkjGfN4b0kPoZn3UJuI0rnZ22yP1fmvUx+05gSqeBV1m+zSuYNVhq7T
WbDiLVvljplLlop6CLXP+2qtvGLIL/1vimISdMBgzSoFZyu6Tqd+jzxgsPaV9BCqee/NjYk6v61K
9cwiUc/STtf1HDpM3b592y7h3Thx5ozK69HLpYWuAwaqS5cv26q7ceb8efVYaReP3iFU8zj1knSw
ZXHMmnCjY00galo7UQfSCM3qQr2H/XFP7ssXx45Yl91ByeCep4mozoH+1fG3xD4tT7x8kwjy8nw
b9ev26V0B6d+7H4zKvudAH537Fjqyz0HdJnHEuzmXq/Wjx0bvNMbv7nhwxsX2aVsWtC8+48aLeap
E7p5wKZi0A2AQRV5nvR4E+uJc+b61kApqInxBgmd/4V5QP/mt18HDC7sRHftmeu5lmhV0rn/ALX2
32bqd4BFnDx7Vi1cWS2uff0IbB47qexxmUj9QutYjupd3tYD6abWBBMrr+apNb0KrNF1+ugCa4ri
XGfwMPPtViavhU3YMOAAAnuUb/R07L0y0Se0adE88ApsXFGff30ynhlJgM51CU6vN9EzgnpvHBFUy
iVraePiwJ53DF5ZTznomEng85kNUd2oJi2Wpr40mmkfN4x4zHfiVFc8Dv8NzuhNq0idilGvA6DGu
eZw078AAQn6ciEk6+rw5VcvjvqNDYP0oIUwaKShrxAuXL1kH4aYuGfMYDc10WF5Ta31hPJ0fcUhr
U/JlINi6c6elRYdBpo6++Yfjx61GNfRm4MD5rJ1j3FoGHnjDSBNarYUgMLyMszKpb7tXpoHfPs8
h3Wp1LzNfNk54XxC1wDGUmYzXYefh6z/cKtVm4EBxa9VQGDzYr3LrUMRjHEKkk7zaFKYQA2hGQU1
z+85NFwpXDrkz3vx10GqxQ6BzeNboBk5n8k4nebRh+k1hWfxTF0D1EyWUs5nv+dgQqKaxzuCdE0i
sHl02NQ8ah0mXr12La3m0f9wik9+wLNTMY/86MPo8yi310fxmT6PWoqG9+DZukYna56mSZt5WWsy
5qVA1rwUyJqXAlnzkiai/gHSD7RkTyihogAAAABJRU5ErkJggg==",
"authenticatorGetInfo": {
    "versions": [ "U2F_V2", "FIDO_2_0" ],
    "extensions": [ "credProtect", "hmac-secret" ],
    "aaguid": "0132d110bf4e4208a403ab4f5f12efe5",
    "options": {
        "plat": false,
        "rk": true,
        "clientPin": true,
        "up": true,
        "uv": true,
        "uvToken": false,
        "config": false
    },
    "maxMsgSize": 1200,
    "pinUvAuthProtocols": [1],
    "maxCredentialCountInList": 16,
    "maxCredentialIdLength": 128,
    "transports": [ "usb", "nfc" ],
    "algorithms": [
        {
            "type": "public-key",
            "alg": -7
        },
        {
            "type": "public-key",
            "alg": -257
        }
    ],
    "maxAuthenticatorConfigLength": 1024,
    "defaultCredProtect": 2,
    "firmwareVersion": 5
}
}
}

```

## 6. Additional Considerations§

### 6.1. Field updates and metadata§

Metadata statements are intended to be stable once they have been published. When authenticators are updated in the field, such updates are expected to improve the authenticator security (for example, improve FRR

or FAR). The authenticatorVersion must be updated if firmware updates fixing severe security issues (e.g. as reported previously) are available.

Note: The metadata statement is assumed to relate to all authenticators having the same authenticator model identifier (AAID/AAGUID/attestationCertificateKeyIdentifiers).

Note: The FIDO Server is recommended to assume increased risk if the authenticatorVersion specified in the metadata statement is newer (higher) than the one present in the authenticator.

Significant changes in authenticator functionality are not anticipated in firmware updates. For example, if an authenticator vendor wants to modify a PIN-based authenticator to use "Speaker Recognition" as a user verification method, the vendor MUST assign a new authenticator model identifier (AAID/AAGUID/attestationCertificateKeyIdentifiers) to this authenticator.

A single authenticator implementation could report itself as two "virtual" authenticators using different authenticator model identifiers (AAIDs/AAGUIDs/attestationCertificateKeyIdentifiers). Such implementations MUST properly (i.e. according to the security characteristics claimed in the metadata) protect UAuth keys and other sensitive data from the other "virtual" authenticator - just as a normal authenticator would do.

Note: Authentication keys (UAuth.pub) registered for one authenticator model (e.g. as identified by AAID/AAGUID/attestationCertificateKeyIdentifiers) cannot be used by authenticators reporting a different authenticator model identifier (AAID/AAGUID/attestationCertificateKeyIdentifiers) - even when running on the same hardware (see section "Authentication Response Processing Rules for FIDO Server" in [\[UAFProtocol\]](#)).

Note: To remain compatible with future versions the FIDO Server SHOULD ignore unrecognized fields when processing any element of an entry. The addition, subtraction or change in interpretation of any fields in an entry of this specification which substantively changes the processing logic of a consumer will only occur alongside an update to the major version number of the specification.

## Index

### Terms defined by this specification

[AAGUID](#)

[aaguid](#)

[aaid](#)

[alternativeDescriptions](#)

[attachmentHint](#)

[attestationCertificateKeyIdentifiers](#)

[attestationRootCertificates](#)

[attestationTypes](#)

[authenticationAlgorithms](#)

[authenticatorGetInfo](#)

[authenticatorVersion](#)

[b](#)

[baDesc](#)

[base](#)

[BiometricAccuracyDescriptor](#)

[bitDepth](#)

[blockSlowdown](#)

[dict-member for BiometricAccuracyDescriptor](#)

[dict-member for CodeAccuracyDescriptor](#)

[dict-member for PatternAccuracyDescriptor](#)

[c](#)

[caDesc](#)

[CodeAccuracyDescriptor](#)

[colorType](#)

[compression](#)

[cryptoStrength](#)

[cxConfigURL](#)

[data](#)

[description](#)

[DisplayPNGCharacteristicsDescriptor](#)

[EcdaaTrustAnchor](#)

[ecdaaTrustAnchors](#)

[ExtensionDescriptor](#)

[fail\\_if\\_unknown](#)

[filter](#)

[friendlyNames](#)

[g](#)

[G1Curve](#)

[height](#)

[iAPARThreshold](#)

[icon](#)

[iconDark](#)

[id](#)

[interlace](#)

[isFreshUserVerificationRequired](#)

[isKeyRestricted](#)

[keyProtection](#)

[legalHeader](#)

[matcherProtection](#)

[maxRetries](#)

[dict-member for BiometricAccuracyDescriptor](#)

[dict-member for CodeAccuracyDescriptor](#)

[dict-member for PatternAccuracyDescriptor](#)

[maxTemplates](#)

[MetadataStatement](#)

[minComplexity](#)

[minLength](#)

[multiDeviceCredentialSupport](#)

[overall claimed cryptographic strength](#)

[paDesc](#)

[PatternAccuracyDescriptor](#)

[plte](#)

[protocolFamily](#)

[providerLogoDark](#)

[providerLogoLight](#)

[publicKeyAlgAndEncodings](#)

[r](#)

[rgbPaletteEntry](#)

[schema](#)

[selfAttestedFAR](#)

[selfAttestedFRR](#)

[supportedExtensions](#)

[sx](#)

[sy](#)

[tag](#)

[tcDisplay](#)

[tcDisplayContentType](#)

[tcDisplayPNGCharacteristics](#)

[upv](#)

[userVerificationDetails](#)

[userVerificationMethod](#)

[VerificationMethodANDCombinations](#)

[VerificationMethodDescriptor](#)

[width](#)

[X](#)

[Y](#)

## Terms defined by reference§

[WebIDL] defines the following terms:

DOMString

boolean

double

octet

unsigned long

unsigned short

## References§

### Normative References§

[ECMA-262]

ECMAScript Language Specification. URL: <https://tc39.es/ecma262/multipage/>

**[FIDOAuthenticatorSecurityRequirements]**

Rolf Lindemann; Dr. Joshua E. Hill; Douglas Biggs. [FIDO Authenticator Security Requirements](https://fidoalliance.org/specs/fido-security-requirements/fido-authenticator-security-requirements-v1.4-fd-20201102.html). November 2020. Final Draft. URL: <https://fidoalliance.org/specs/fido-security-requirements/fido-authenticator-security-requirements-v1.4-fd-20201102.html>

**[FIDOBiometricsRequirements]**

Stephanie Schuckers; et al. [FIDO Biometrics Requirements](https://fidoalliance.org/specs/biometric/requirements/Biometrics-Requirements-v2.0-fd-20201006.html). October 2020. URL: <https://fidoalliance.org/specs/biometric/requirements/Biometrics-Requirements-v2.0-fd-20201006.html>

**[FIDOCATP]**

C. Brand; et al. [FIDO 2.0: Client To Authenticator Protocol](https://fidoalliance.org/specs/fido-v2.0-ps-20190130/fido-client-to-authenticator-protocol-v2.0-ps-20190130.html). 30 January 2019. URL: <https://fidoalliance.org/specs/fido-v2.0-ps-20190130/fido-client-to-authenticator-protocol-v2.0-ps-20190130.html>

**[FIDOMetadataService]**

B. Jack; R. Lindemann; Y. Ackermann. [FIDO Metadata Service](https://fidoalliance.org/specs/mds/fido-metadata-service-v3.1-ps-20250521.html). 21 May 2025. Proposed Standard. URL: <https://fidoalliance.org/specs/mds/fido-metadata-service-v3.1-ps-20250521.html>

**[FIDORRegistry]**

R. Lindemann; et al. [FIDO Registry of Predefined Values](https://fidoalliance.org/specs/common-specs/fido-registry-v2.2-ps-20220523.html). 23 May 2022. Proposed Standard. URL: <https://fidoalliance.org/specs/common-specs/fido-registry-v2.2-ps-20220523.html>

**[ISOIEC-19795-1]**

[ISO/IEC 19795-1:2021 Information technology — Biometric performance testing and reporting — Part 1: Principles and framework](https://www.iso.org/standard/73515.html). 2021. URL: <https://www.iso.org/standard/73515.html>

**[ISOIEC-30107-3]**

[ISO/IEC 30107-3:2017 Information technology — Biometric presentation attack detection — Part 3: Testing and reporting](https://www.iso.org/obp/ui/#iso:std:iso-iec:30107:-3:ed-1:v1:en). 2017. URL: <https://www.iso.org/obp/ui/#iso:std:iso-iec:30107:-3:ed-1:v1:en>

**[PNG]**

Chris Lilley; et al. [Portable Network Graphics \(PNG\) Specification \(Third Edition\)](https://www.w3.org/png/). URL: <https://www.w3.org/png/>

**[RFC2049]**

N. Freed; N. Borenstein. [Multipurpose Internet Mail Extensions \(MIME\) Part Five: Conformance Criteria and Examples \(RFC 2049\)](https://tools.ietf.org/html/rfc2049). November 1996. November 1996. URL: <https://tools.ietf.org/html/rfc2049>

**[RFC2397]**

L. Masinter. [The "data" URL scheme](https://www.rfc-editor.org/rfc/rfc2397). August 1998. Proposed Standard. URL: <https://www.rfc-editor.org/rfc/rfc2397>

**[RFC4122]**

P. Leach. [A Universally Unique IDentifier \(UUID\) URN Namespace](https://tools.ietf.org/html/rfc4122). July 2005. URL: <https://tools.ietf.org/html/rfc4122>

**[SVG11]**

Erik Dahlström; et al. [Scalable Vector Graphics \(SVG\) 1.1 \(Second Edition\)](https://www.w3.org/TR/SVG11/). 16 August 2011. REC. URL: <https://www.w3.org/TR/SVG11/>

**[UAFProtocol]**

R. Lindemann; et al. [FIDO UAF Protocol Specification v1.2](https://fidoalliance.org/specs/fido-uaf-v1.2-ps-20201020/fido-uaf-protocol-v1.2-ps-20201020.html). Proposed Standard. URL: <https://fidoalliance.org/specs/fido-uaf-v1.2-ps-20201020/fido-uaf-protocol-v1.2-ps-20201020.html>

**[WebAuthn]**

Dirk Balfanz (Google); et al. [Web Authentication: An API for accessing Public Key Credentials Level 2](https://www.w3.org/TR/webauthn-2/). 8 April 2021. TR. URL: <https://www.w3.org/TR/webauthn-2/>

**[WebIDL]**

Edgar Chen; Timothy Gu. [Web IDL Standard](https://webidl.spec.whatwg.org/). Living Standard. URL: <https://webidl.spec.whatwg.org/>

**[WebIDL-ED]**

Cameron McCormack. [Web IDL](http://heycam.github.io/webidl/). 13 November 2014. Editor's Draft. URL: <http://heycam.github.io/webidl/>

**Informative References**

**[AndroidCompatibilityDefinition]**

[Android 14 Compatibility Definition](https://source.android.com/docs/compatibility/14/android-14-cdd). URL: <https://source.android.com/docs/compatibility/14/android-14-cdd>

**[AndroidUnlockPattern]**

[Android Unlock Pattern Security Analysis](http://www.sinustrom.info/2012/05/21/android-unlock-pattern-security-analysis/). Published. URL: <http://www.sinustrom.info/2012/05/21/android-unlock-pattern-security-analysis/>

**[ApplePlatformSecurity]**

[Apple Platform Security](https://support.apple.com/guide/security/welcome/web). URL: <https://support.apple.com/guide/security/welcome/web>

**[FIDOEcdaaAlgorithm]**

R. Lindemann; et al. [FIDO ECDAA Algorithm](https://fidoalliance.org/specs/fido-v2.0-id-20180227/fido-ecdaa-algorithm-v2.0-id-20180227.html). 23 May 2022. Proposed Standard. URL: <https://fidoalliance.org/specs/fido-v2.0-id-20180227/fido-ecdaa-algorithm-v2.0-id-20180227.html>

**[FIDOGlossary]**

R. Lindemann; et al. [FIDO Technical Glossary](https://fidoalliance.org/specs/common-specs/fido-glossary-v2.1-ps-20220523.html). 23 May 2022. Proposed Standard. URL: <https://fidoalliance.org/specs/common-specs/fido-glossary-v2.1-ps-20220523.html>

**[FIDOKeyAttestation]**

[FIDO 2.0: Key attestation format](https://fidoalliance.org/specs/fido-v2.0-ps-20150904/fido-key-attestation-v2.0-ps-20150904.html). URL: <https://fidoalliance.org/specs/fido-v2.0-ps-20150904/fido-key-attestation-v2.0-ps-20150904.html>

**[iPhonePasscodes]**

Daniel Amitay. [Most Common iPhone Passcodes](http://danielamitay.com/blog/2011/6/13/most-common-iphone-passcodes). URL: <http://danielamitay.com/blog/2011/6/13/most-common-iphone-passcodes>

**[ISO3166]**

[Codes for the representation of names of countries and their subdivisions — Part 1: Country code](https://www.iso.org/standard/72482.html). August 2020. Published. URL: <https://www.iso.org/standard/72482.html>

**[ITU-X690-2008]**

[X.690: Information technology - ASN.1 encoding rules: Specification of Basic Encoding Rules \(BER\), Canonical Encoding Rules \(CER\) and Distinguished Encoding Rules \(DER\). \(T-REC-X.690-200811\).](https://www.itu.int/rec/T-REC-X.690-200811-S) November 2008. URL: <https://www.itu.int/rec/T-REC-X.690-200811-S>

**[MoreTopWorstPasswords]**

Mark Burnett. [10000 Top Passwords](https://xato.net/passwords/more-top-worst-passwords/). URL: <https://xato.net/passwords/more-top-worst-passwords/>

**[RFC4648]**

S. Josefsson. [The Base16, Base32, and Base64 Data Encodings \(RFC 4648\)](http://www.ietf.org/rfc/rfc4648.txt). October 2006. URL: <http://www.ietf.org/rfc/rfc4648.txt>

**[RFC5280]**

D. Cooper; et al. [Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List \(CRL\) Profile](https://tools.ietf.org/html/rfc5280). May 2008. URL: <https://tools.ietf.org/html/rfc5280>

**[RFC5646]**

A. Phillips, Ed.; M. Davis, Ed.. [Tags for Identifying Languages](https://www.rfc-editor.org/rfc/rfc5646). September 2009. Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc5646>

**[UAFAuthnrCommands]**

D. Baghdasaryan; et al. [FIDO UAF Authenticator Commands](https://fidoalliance.org/specs/fido-uaf-v1.2-ps-20201020/fido-uaf-authnr-cmds-v1.2-ps-20201020.html). Proposed Standard. URL: <https://fidoalliance.org/specs/fido-uaf-v1.2-ps-20201020/fido-uaf-authnr-cmds-v1.2-ps-20201020.html>

**[UAFRegistry]**

R. Lindemann; D. Baghdasaryan; B. Hill. [FIDO UAF Registry of Predefined Values](https://fidoalliance.org/specs/fido-uaf-v1.2-ps-20201020/fido-uaf-reg-v1.2-ps-20201020.html). Proposed Standard. URL: <https://fidoalliance.org/specs/fido-uaf-v1.2-ps-20201020/fido-uaf-reg-v1.2-ps-20201020.html>

## IDL Index

```
typedef DOMString AAGUID;

dictionary CodeAccuracyDescriptor {
    required unsigned short base;
    required unsigned short minLength;
    unsigned short      maxRetries;
    unsigned short      blockSlowdown;
```

```

};

dictionary BiometricAccuracyDescriptor {
    double          selfAttestedFRR;
    double          selfAttestedFAR;
    double          iAPARThreshold;
    unsigned short  maxTemplates;
    unsigned short  maxRetries;
    unsigned short  blockSlowdown;
};

dictionary PatternAccuracyDescriptor {
    required unsigned long minComplexity;
    unsigned short      maxRetries;
    unsigned short      blockSlowdown;
};

dictionary VerificationMethodDescriptor {
    DOMString          userVerificationMethod;
    CodeAccuracyDescriptor  caDesc;
    BiometricAccuracyDescriptor  baDesc;
    PatternAccuracyDescriptor  paDesc;
};

typedef VerificationMethodDescriptor[] VerificationMethodANDCombinations;

dictionary rgbPaletteEntry {
    required unsigned short r;
    required unsigned short g;
    required unsigned short b;
};

dictionary DisplayPNGCharacteristicsDescriptor {
    required unsigned long width;
    required unsigned long height;
    required octet      bitDepth;
    required octet      colorType;
    required octet      compression;
    required octet      filter;
    required octet      interlace;
    rgbPaletteEntry[]  plte;
};

dictionary EcdaaTrustAnchor {
    required DOMString X;
    required DOMString Y;
    required DOMString c;
    required DOMString sx;
    required DOMString sy;
    required DOMString G1Curve;
};

dictionary ExtensionDescriptor {
    required DOMString id;
    unsigned short  tag;
    DOMString       data;
    required boolean fail_if_unknown;
};

dictionary MetadataStatement {
    DOMString          legalHeader;
    AAID              aaid;
    AAGUID             aauid;
};

```

```
DOMString[]  
FriendlyNames  
required DOMString  
AlternativeDescriptions  
required unsigned long  
required DOMString  
required unsigned short  
required Version[]  
required DOMString[]  
required DOMString[]  
required DOMString[]  
VerificationMethodANDCombinations[]  
required DOMString[]  
boolean  
boolean  
required DOMString[]  
unsigned short  
DOMString[]  
required DOMString[]  
DOMString  
DisplayPNGCharacteristicsDescriptor[]  
required DOMString[]  
EcdaaTrustAnchor[]  
DOMString  
DOMString  
DOMString  
DOMString  
ExtensionDescriptor[]  
DOMString  
AuthenticatorGetInfo  
DOMString  
};  
attestationCertificateKeyIdentifiers;  
friendlyNames;  
description;  
alternativeDescriptions;  
authenticatorVersion;  
protocolFamily;  
schema;  
upv;  
authenticationAlgorithms;  
publicKeyAlgAndEncodings;  
attestationTypes;  
userVerificationDetails;  
keyProtection;  
isKeyRestricted;  
isFreshUserVerificationRequired;  
matcherProtection;  
cryptoStrength;  
attachmentHint;  
tcDisplay;  
tcDisplayContentType;  
tcDisplayPNGCharacteristics;  
attestationRootCertificates;  
ecdaaTrustAnchors;  
icon;  
iconDark;  
providerLogoLight;  
providerLogoDark;  
supportedExtensions;  
multiDeviceCredentialSupport;  
authenticatorGetInfo;  
cxConfigURL;
```