



FIDO U2F Raw Message Formats

FIDO Alliance Proposed Standard 11 April 2017

This version:

<https://fidoalliance.org/specs/fido-u2f-v1.2-ps-20170411/fido-u2f-raw-message-formats-v1.1-v1.2-ps-20170411.html>

Previous version:

<https://fidoalliance.org/specs/fido-u2f-raw-message-formats-v1.1-RD-20140209.html>

Editors:

[Dirk Balfanz, Google, Inc.](#)
[Jakob Ehrensvar, Yubico, Inc](#)
[Juan Lang, Google, Inc.](#)

The English version of this specification is the only normative version. Non-normative [translations](#) may also be available.

Copyright © 2013-2017 [FIDO Alliance](#) All Rights Reserved.

Abstract

Status of This Document

This section describes the status of this document at the time of its publication. Other documents may supersede this document. A list of current FIDO Alliance publications and the latest revision of this technical report can be found in the [FIDO Alliance specifications index](https://www.fidoalliance.org/specifications/) at <https://www.fidoalliance.org/specifications/>.

This document was published by the [FIDO Alliance](#) as a Proposed Standard. If you wish to make comments regarding this document, please [Contact Us](#). All comments are welcome.

Implementation of certain elements of this Specification may require licenses under third party intellectual property rights, including without limitation, patent rights. The FIDO Alliance, Inc. and its Members and any other contributors to the Specification are not, and shall not be held, responsible in any manner for identifying or failing to identify any or all such third party intellectual property rights.

THIS FIDO ALLIANCE SPECIFICATION IS PROVIDED "AS IS" AND WITHOUT ANY WARRANTY OF ANY KIND, INCLUDING, WITHOUT LIMITATION, ANY EXPRESS OR IMPLIED WARRANTY OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This document has been reviewed by FIDO Alliance Members and is endorsed as a Proposed Standard. It is a stable document and may be used as reference material or cited from another document. FIDO Alliance's role in making the Recommendation is to draw attention to the specification and to promote its widespread deployment.

Table of Contents

- 1. [Notation](#)
 - 1.1 [Key Words](#)
- 2. [Introduction](#)
- 3. [U2F message framing](#)
 - 3.1 [Request Message Framing](#)
 - 3.1.1 [Command and parameter values](#)
 - 3.1.2 [Short Encoding](#)
 - 3.1.3 [Extended Length Encoding](#)
 - 3.2 [Response Message Framing](#)
 - 3.3 [Status Codes](#)
- 4. [Registration Messages](#)
 - 4.1 [Registration Request Message - U2F_REGISTER](#)
 - 4.2 [Registration Response Message: Error: Test-of-User-Presence Required](#)
 - 4.3 [Registration Response Message: Success](#)
- 5. [Authentication Messages](#)
 - 5.1 [Authentication Request Message - U2F_AUTHENTICATE](#)
 - 5.2 [Authentication Response Message: Error: Test-of-User-Presence Required](#)
 - 5.3 [Authentication Response Message: Error: Bad Key Handle](#)
 - 5.4 [Authentication Response Message: Success](#)
- 6. [Other Messages](#)
 - 6.1 [GetVersion Request and Response - U2F_VERSION](#)
 - 6.2 [Extensions and vendor-specific messages](#)
- 7. [Client Data](#)
 - 7.1 [Dictionary `clientData` Members](#)
 - 7.2 [Dictionary `JwkKey` Members](#)

- 8. Examples
 - 8.1 Registration Example
 - 8.2 Authentication Example
- 9. Implementation Considerations
- A. References
 - A.1 Normative references
 - A.2 Informative references

1. Notation

Type names, attribute names and element names are written as `code`.

String literals are enclosed in “”, e.g. “UAF-TLV”.

In formulas we use “|” to denote byte wise concatenation operations.

DOM APIs are described using the ECMAScript [ECMA-262] bindings for WebIDL [WebIDL].

U2F specific terminology used in this document is defined in [FIDOGlossary].

Symbolic constants such as `U2F_REGISTER` which are referred to when defining messages in this documents have their values defined in (See [U2FHeader] in bibliography).

1.1 Key Words

The key words “**must**”, “**must not**”, “**required**”, “**shall**”, “**shall not**”, “**should**”, “**should not**”, “**recommended**”, “**may**”, and “**optional**” in this document are to be interpreted as described in [RFC2119].

2. Introduction

Note: Reading the 'FIDO U2F Overview' (see [U2FOverview] in bibliography) is recommended as a background for this document.

U2F Tokens provide cryptographic assertions that can be verified by relying parties. Typically, the relying party is a web server, and the cryptographic assertions are used as second-factors (in addition to passwords) during user authentication.

U2F Tokens are typically small special-purpose devices that aren't directly connected to the Internet (and hence, able to talk directly to the relying party). Therefore, they rely on a FIDO Client to relay messages between the token and the relying party. Typically, the FIDO Client is a web browser.

The U2F protocol supports two operations, registration and authentication. The registration operation introduces the relying party to a freshly-minted keypair that is under control of the U2F token. The authentication operation proves possession of a previously-registered keypair to the relying party. Both the registration and authentication operation consist of three phases:

1. Setup: In this phase, the FIDO Client contacts the relying party and obtains a challenge. Using the challenge (and possibly other data obtained from the relying party and/or prepared by the FIDO Client itself), the FIDO Client prepares a request message for the U2F Token.
2. Processing: In this phase, the FIDO Client sends the request message to the token, and the token performs some cryptographic operations on the message, creating a response message. This response message is sent to the FIDO Client.
3. Verification: In this phase, the FIDO Client transmits the token's response message, along with other data necessary for the relying party to verify the token response, to the relying party. The relying party then processes the token response and verifies its correctness. A correct registration response will cause the relying party to register a new public key for a user, while a correct authentication response will cause the relying party to accept that the client is in possession of the corresponding private key.




Fig. 1 Three phases of Registration and Authentication

Above is a picture illustrating the three phases.

At the heart of the U2F protocol are the request messages sent to the U2F token, and the response messages received from the U2F token.¹

Note that the request message is usually obtained by the FIDO client from the relying party during the setup phase, and therefore reaches the FIDO client as part of an HTTP response. Similarly, the response message that is processed by the relying party during the verification phase is sent by the FIDO Client to the relying party in an HTTP request. Beware the possibility of confusion when talking about requests and responses!

Request messages are created by the relying party and consumed by the U2F token. Response messages are created by the U2F token and consumed by the relying party.

As the messages flow from relying party (through the FIDO Client) to the U2F token and back, they undergo various transformations and encodings. Some of these transformations and encodings are up to the individual implementations and are not standardized as part of FIDO U2F. For example, FIDO U2F does not prescribe how request and response messages are encoded between the FIDO Client and the relying party.

However, to ensure that U2F tokens from different vendors can work across U2F-compliant web sites certain encodings are standardized:

1. FIDO U2F standardizes a Javascript API that prescribes how a web application can pass request messages into the FIDO Client (in the case where the web browser is the FIDO Client), and what the encoding of the response messages is.
2. FIDO U2F standardizes how request and response messages are to be encoded when sent over from the client over the USB, NFC, Bluetooth and Bluetooth Low-Energy transports to U2F tokens. In addition to specifying the encoding, the transport level specification also specifies the

format for control messages to the tokens and the format for the error responses from the tokens.

In this document we describe the "raw", or canonical, format of the messages, i.e., without regard to the various encodings that are prescribed in U2F transport standards or that implementors might choose when sending messages around. The raw format of the messages is important to know for two reasons:

1. The encoding of messages and parameters described elsewhere may refer to the raw messages described in this document. For example, a Javascript API might refer to a parameter of a function as the Base64-encoding of a raw registration response message. It is this document that describes what the raw registration response message looks like.
2. Cryptographic signatures are calculated over raw data. For example, the standard might prescribe that a certain cryptographic signature is taken over bytes 5 through 60 of a certain raw message. The implementor therefore has to know how what the raw message looks like.

3. U2F message framing

The U2F protocol is based on a request-response mechanism, where a requester sends a request message to a U2F device, which always results in a response message being sent back from the U2F device to the requester.

The request message has to be "framed" to send to the lower layer. Taking the signature request as an example, the "framing" is a way for the FIDO client to tell the lower transport layer that it is sending a signature request and then send the raw message contents. The framing also specifies how the transport will carry back the response raw message and any meta-information such as an error code if the command failed.

Framing is defined based on the ISO7816-4:2005 APDU format.

3.1 Request Message Framing

The raw request message is framed as a command APDU. At a high level, APDUs are framed in the following way:

CLA INS P1 P2 [L_c <request-data>] [L_e]

Where:

- **CLA**: Reserved to be used by the underlying transport protocol (if applicable). The host application shall set this byte to zero.
- **INS**: U2F command code, defined in the following sections.
- **P1, P2**: Parameter 1 and 2, defined by each command.
- **L_c** : The length of the **request-data**. If there are no request data bytes, **L_c** is omitted.
- **L_e** : The maximum expected length of the response data. If no response data are expected, **L_e** may be omitted.

The precise format of the APDU depends on the encoding choice. There are two different encodings allowed for an APDU: **short** and **extended length**. The differences are in the way the length of the request data, **L_c** , and the maximum length of the expected response, **L_e** , are encoded.

The choice of encoding varies depending on the needs of the individual transport. Refer to the transport-specific encoding documents for which encodings are allowed with each transport.

3.1.1 Command and parameter values

Command	INS	P1	P2
U2F_REGISTER	0x01	0x00	0x00
U2F_AUTHENTICATE	0x02	0x0310x0710x08	0x00
U2F_VERSION	0x03	0x00	0x00
VENDOR SPECIFIC	0x40-0xbf	NA	NA

3.1.2 Short Encoding

In **short encoding**, the maximum length of request-data is 255 bytes. **L_c** is encoded in the following way:

Let $N_c = | \text{<request-data>} |$. If N_c is 0, **L_c** is omitted. Otherwise, **L_c** is encoded as a single byte containing the value of N_c .

If the instruction is not expected to yield any response bytes, **L_e** may be omitted. Otherwise, in **short encoding**, **L_e** is encoded in the following way:

Let N_e = the maximum length of the response data. In **short encoding**, the maximum value of N_e is 256 bytes.

For values of N_e between 1 and 255, **L_e** contains the value of N_e . When $N_e = 256$, **L_e** contains the value 0.

3.1.3 Extended Length Encoding

In **extended length encoding**, the maximum length of request-data is 65 535 bytes. **L_c** is encoded in the following way:

Let $N_c = | \text{<request-data>} |$. If N_c is 0, **L_c** is omitted. Otherwise, **L_c** is encoded as:

0 MSB(N_c) LSB(N_c)

Where **MSB(N_c)** is the most significant byte of N_c , and **LSB(N_c)** is the least significant byte of N_c .

In other words, the request-data are preceded by three length bytes, a byte with value 0 followed by the length of request-data, in big-endian order.

If the instruction is not expected to yield any response bytes, **L_e** may be omitted. Otherwise, in **extended length encoding**, **L_e** is encoded in the following way:

Let N_e = the maximum length of the response data. In **extended length encoding**, the maximum value of N_e is 65 536 bytes.

For values of N_e between 1 and 65 535, inclusive, let $L_{e1} = \text{MSB}(N_e)$, and $L_{e2} = \text{LSB}(N_e)$, where $\text{MSB}(N_e)$ is the most significant byte of N_e , and $\text{LSB}(N_e)$ is the least significant byte of N_e .

When $N_e = 65\,536$, let $L_{e1} = 0$ and $L_{e2} = 0$.

When L_c is present, i.e. if $N_c > 0$, L_e is encoded as:

$L_{e1} L_{e2}$

When L_c is absent, i.e. if $N_c = 0$, L_e is encoded as:

$0 L_{e1} L_{e2}$

In other words, L_e has a single-byte prefix of 0 when L_c is absent.

3.2 Response Message Framing

The raw response data is framed as a response APDU:

<response-data> SW₁ SW₂

Where **SW₁** and **SW₂** are the status word bytes 1 and 2, respectively, forming a 16-bit status word, defined below. SW₁ is the most-significant byte, and SW₂ is the least-significant byte.

3.3 Status Codes

The following ISO7816-4 defined status words have a special meaning in U2F:

- **SW_NO_ERROR (0x9000)**: The command completed successfully without error.
- **SW_CONDITIONS_NOT_SATISFIED (0x6985)**: The request was rejected due to test-of-user-presence being required.
- **SW_WRONG_DATA (0x6A80)**: The request was rejected due to an invalid key handle.
- **SW_WRONG_LENGTH (0x6700)**: The length of the request was invalid.
- **SW_CLA_NOT_SUPPORTED (0x6E00)**: The Class byte of the request is not supported.
- **SW_INS_NOT_SUPPORTED (0x6D00)**: The Instruction of the request is not supported.

Each implementation may define any other vendor-specific status codes, providing additional information about an error condition. Only the error codes listed above will be handled by U2F FIDO Client, where others will be seen as general errors and logging of these is optional.

4. Registration Messages

4.1 Registration Request Message - U2F_REGISTER




Fig. 2 Registration Request Message

This message is used to initiate a U2F token registration. The FIDO Client first contacts the relying party to obtain a challenge, and then constructs the registration request message. The registration request message has two parts:

- The **challenge parameter** [32 bytes]. The challenge parameter is the SHA-256 hash of the Client Data, a stringified JSON data structure that the FIDO Client prepares. Among other things, the Client Data contains the challenge from the relying party (hence the name of the parameter). See below for a detailed explanation of Client Data.
- The **application parameter** [32 bytes]. The application parameter is the SHA-256 hash of the UTF-8 encoding of the application identity of the application requesting the registration. (See [FIDOAppIDAndFacets] in bibliography for details.)

4.2 Registration Response Message: Error: Test-of-User-Presence Required

This is an error message that is output by the U2F token if no test-of-user-presence could be obtained by the U2F token. The error message details are specified in the framing for the underlying transport (see Section "U2F Message Framing" above).

4.3 Registration Response Message: Success




Fig. 3 Registration Response Message

This message is output by the U2F token once it created a new keypair in response to the registration request message. Note that U2F tokens **should** verify user presence before returning a registration response success message (otherwise they **should** return a test-of-user-presence-required message - see above). Its raw representation is the concatenation of the following:

- A **reserved byte** [1 byte], which for legacy reasons has the value 0x05.
- A **user public key** [65 bytes]. This is the (uncompressed) x,y-representation of a curve point on the P-256 NIST elliptic curve.
- A **key handle length byte** [1 byte], which specifies the length of the key handle (see below). The value is unsigned (range 0-255).
- A **key handle** [length specified in previous field]. This is a handle that allows the U2F token to identify the generated key pair. U2F tokens **may** wrap the generated private key and the application id it was generated for, and output that as the key handle.
- An **attestation certificate** [variable length]. This is a certificate in X.509 DER format. Parsing of the X.509 certificate unambiguously establishes its ending. The remaining bytes in the message are
- a **signature** [variable length, 71-73 bytes]. This is an ECDSA signature (on P-256) over the following byte string:
 - A *byte reserved for future use* [1 byte] with the value 0x00.
 - The *application parameter* [32 bytes] from the registration request message.
 - The *challenge parameter* [32 bytes] from the registration request message.
 - The above *key handle* [variable length]. (Note that the key handle length is not included in the signature base string. This doesn't cause confusion in the signature base string, since all other parameters in the signature base string are fixed-length.)
 - The above *user public key* [65 bytes].

The signature is encoded in ANSI X9.62 format (see [\[ECDSA-ANSI\]](#) in bibliography).

The signature is to be verified by the relying party using the public key certified in the attestation certificate. The relying party should also verify that the attestation certificate was issued by a trusted certification authority. The exact process of setting up trusted certification authorities is to be defined by the FIDO Alliance and is outside the scope of this document.

Once the relying party verifies the signature, it should store the public key and key handle so that they can be used in future authentication operations.

5. Authentication Messages

5.1 Authentication Request Message - U2F_AUTHENTICATE




Fig. 4 Authentication Request Message

This message is used to initiate a U2F token authentication. The FIDO Client first contacts the relying party to obtain a challenge, and then constructs the authentication request message. The authentication request message has five parts:

- Control byte (P1). The control byte is determined by the FIDO Client - the relying party cannot specify its value. The FIDO Client will set the control byte to one of the following values:
 - 0x07 ("check-only")**: if the control byte is set to 0x07 by the FIDO Client, the U2F token is supposed to simply check whether the provided key handle was originally created by this token, and whether it was created for the provided application parameter. If so, the U2F token **must** respond with an authentication response message: error: test-of-user-presence-required (note that despite the name this signals a success condition). If the key handle was not created by this U2F token, or if it was created for a different application parameter, the token **must** respond with an authentication response message: error: bad-key-handle.
 - 0x03 ("enforce-user-presence-and-sign")**: If the FIDO client sets the control byte to 0x03, then the U2F token is supposed to perform a real signature and respond with either an authentication response message: success or an appropriate error response (see below). The signature **should** only be provided if user presence could be validated.
 - 0x08 ("dont-enforce-user-presence-and-sign")**: If the FIDO client sets the control byte to 0x08, then the U2F token is supposed to perform a real signature and respond with either an authentication response message: success or an appropriate error response (see below). The signature **may** be provided without validating user presence.

Other control byte values are reserved for future use.

During registration, the FIDO Client **may** send authentication request messages to the U2F token to figure out whether the U2F token has already been registered. In this case, the FIDO client will use the check-only value for the control byte. In all other cases (i.e., during authentication), the FIDO Client **must** use the enforce-user-presence-and-sign or don't-enforce-user-presence-and-sign values.

- The **challenge parameter** [32 bytes]. The challenge parameter is the SHA-256 hash of the Client Data, a stringified JSON data structure that the FIDO Client prepares. Among other things, the Client Data contains the challenge from the relying party (hence the name of the parameter). See below for a detailed explanation of Client Data.
- The **application parameter** [32 bytes]. The application parameter is the SHA-256 hash of the UTF-8 encoding of the application identity of the application requesting the authentication as provided by the relying party.
- A **key handle length byte** [1 byte], which specifies the length of the key handle (see below). The value is unsigned (range 0-255).
- A **key handle** [length specified in previous field]. The key handle. This is provided by the relying party, and was obtained by the relying party during registration.

5.2 Authentication Response Message: Error: Test-of-User-Presence Required

This is an error message that is output by the U2F token if no test-of-user-presence could be obtained by the U2F token. The error message details are specified in the framing for the underlying transport (see Section "U2F Message Framing" above).

5.3 Authentication Response Message: Error: Bad Key Handle

This is an error message that is output by the U2F token if the provided key handle was not originally created by this token, or if the provided key handle was created by this token, but for a different application parameter. The error message details are specified in the framing for the underlying transport (see Section "U2F Message Framing" above).

5.4 Authentication Response Message: Success




Fig. 5 Authentication Response Message: Success

This message is output by the U2F token after processing/signing the authentication request message described above. Its raw representation is the concatenation of the following:

- A **user presence byte** [1 byte]. Bit 0 indicates whether user presence was verified. If Bit 0 is set to 1, then user presence was verified. If Bit 0 is set to 0, then user presence was not verified. The values of Bit 1 through 7 **shall** be 0; different values are reserved for future use.




Fig. 6 User Presence Byte Layout

- A **counter** [4 bytes]. This is the big-endian representation of a counter value that the U2F token increments every time it performs an authentication operation. (See Implementation Considerations [U2FImplCons] for more detail.)
- a **signature**. This is a ECDSA signature (on P-256) over the following byte string:
 - The *application parameter* [32 bytes] from the authentication request message.
 - The above *user presence byte* [1 byte].
 - The above *counter* [4 bytes].
 - The *challenge parameter* [32 bytes] from the authentication request message.

The signature is encoded in ANSI X9.62 format (see [ECDSA-ANSI] in bibliography).

The signature is to be verified by the relying party using the public key obtained during registration.

6. Other Messages

6.1 GetVersion Request and Response - U2F_VERSION

The FIDO Client can query the U2F token about the U2F protocol version that it implements. The protocol version described in this document is U2F_V2.

The response message's raw representation is the ASCII representation of the string 'U2F_V2' (without quotes, and without any NUL terminator).

The command takes no flags, i.e. P1 and P2 are 0, and takes no data as input. As a result, the complete layout of this command in **short** encoding is, in hexadecimal form:

```
CLA INS P1 P2 Le
00 03 00 00 00
```

The layout of this command in **extended length** encoding is, in hexadecimal form:

```
CLA INS P1 P2 Le
00 03 00 00 00 00 00
```

6.2 Extensions and vendor-specific messages

Command codes in the range between **U2F_VENDOR_FIRST** and **U2F_VENDOR_LAST** may be used for vendor-specific implementations. For example, the vendor may choose to put in some testing commands. Note that the FIDO client will never generate these commands. All other command codes are RFU and may not be used.

7. Client Data

Term	Definition
websafe-base64 encoding	This is the "Base 64 Encoding with URL and Filename Safe Alphabet" from Section 5 in [RFC4648] without padding.
stringified javascript object	This is the JSON object (i.e., a string starting with "{" and ending with "}") whose keys are the property names of the javascript object, and whose values are the corresponding property values. Only "data objects" can be stringified, i.e., only objects whose property names and values are supported in JSON .

The registration and authentication request messages contain a challenge parameter, which is defined as the SHA-256 hash of a (UTF8 representation of a) stringified JSON data structure that the FIDO client has to prepare. The FIDO Client **must** send the Client Data (rather than its hash - the challenge parameter) to the relying party during the verification phase, where the relying party can re-generate the challenge parameter (by hashing the client data), which is necessary in order to verify the signature both on the registration response message and authentication response message.

In the case where the FIDO Client is a web browser, the client data is defined as follows (in WebIDL):

WebIDL

```
dictionary ClientData {
  DOMString      typ;
  DOMString      challenge;
  DOMString      origin;
  (DOMString or JwkKey) cid_pubkey;
```

```
};
```

7.1 Dictionary `ClientData` Members

`typ` of type `DOMString`
the constant 'navigator.id.getAssertion' for authentication, and 'navigator.id.finishEnrollment' for registration

`challenge` of type `DOMString`
the websafe-base64-encoded challenge provided by the relying party

`origin` of type `DOMString`
the facet id of the caller, i.e., the web origin of the relying party.
(Note: this might be more accurately called 'facet_id', but for compatibility with existing implementations within Chrome we keep the legacy name.)

`cid_pubkey` of type (`DOMString` or `JwkKey`)
The Channel ID public key used by this browser to communicate with the above origin. This parameter is optional, and missing if the browser doesn't support Channel ID. It is present and set to the constant 'unused' if the browser supports Channel ID, but is not using Channel ID to talk to the above origin (presumably because the origin server didn't signal support for the Channel ID TLS extension).

Otherwise (i.e., both browser and origin server at the above origin support Channel ID), it is present and of type `JwkKey`.

The `JwkKey` is a dictionary representing the public key used by a browser for the Channel ID TLS extension. The current version of the Channel ID draft prescribes the algorithm ([[ECDSA-ANSI](#)] in bibliography) and curve used, so the dictionary will have the following parameters

WebIDL

```
dictionary JwkKey {  
  DOMString kty;  
  DOMString crv;  
  DOMString x;  
  DOMString y;  
};
```

7.2 Dictionary `JwkKey` Members

`kty` of type `DOMString`
signature algorithm used for Channel ID, i.e., the constant 'EC'

`crv` of type `DOMString`
Elliptic curve on which this public key is defined, i.e., the constant 'P-256'

`x` of type `DOMString`
websafe-base64-encoding of the x coordinate of the public key (big-endian, 32-byte value)

`y` of type `DOMString`
websafe-base64-encoding of the y coordinate of the public key (big-endian, 32-byte value)

8. Examples

8.1 Registration Example

Assume we have a U2F token with the following private attestation key:

```
f3fccc0d00d8031954f90864d43c247f4bf5f0665c6b50cc17749a27d1cf7664
```

the corresponding public key:

```
048d617e65c9508e64bcc5673ac82a6799da3c1446682c258c463ffdf58dfd2fa3e6c378b53d795c4a4dfbf4199edd7862f23abaf0203b4b8911ba0569994e101
```

and the following attestation cert:

```
[  
[  
Version: V3  
Subject: CN=PilotGnubby-0.4.1-47901280001155957352 Signature Algorithm: SHA256withECDSA, OID = 1.2.840.10045.4.3.2  
Key: EC Public Key  
X:  
8d617e65c9508e64bcc5673ac82a6799da3c1446682c258c463ffdf58dfd2fa Y:  
3e6c378b53d795c4a4dfbf4199edd7862f23abaf0203b4b8911ba0569994e101  
Validity: [From: Tue Aug 14 11:29:32 PDT 2012, To: Wed Aug 14 11:29:32 PDT 2013]  
Issuer: CN=Gnubby Pilot  
SerialNumber: [ 47901280 00115595 7352 ] ]  
Algorithm: [SHA256withECDSA]  
Signature:  
0000: 30 44 02 20 60 CD B6 06 1E 9C 22 26 2D 1A AC 1D 0D. `....."&-...  
0010: 96 D8 C7 08 29 B2 36 65 31 DD A2 68 83 2C B8 36 .....6e1..h.,.6  
0020: BC D3 0D FA 02 20 63 1B 14 59 F0 9E 63 30 05 57 ..... c..Y..c0.W  
0030: 22 C8 D8 9B 7F 48 88 3B 90 89 B8 8D 60 D1 D9 79 "....H.;....`..y  
0040: 59 02 B3 04 10 DF Y.....  
]
```

The attestation cert in hex form:

```
3082013c3081e4a03020102020a47901280001155957352300a06082a8648ce3d0403023017311530130603550403130c476e756262792050696c6f74301e170d3132303831
```

Now let's assume that we use the following client data

```
{ "typ": "navigator.id.finishEnrollment", "challenge": "vqrS6WXDe1JUs5_c3i4-LkKIHRr-3XVb3azuA5TifHo", "cid_pubkey": {"kty": "EC", "crv": "P-256", "x": "HzQwlFX7Q4S5MtCCnZUNBw3RMzPO9tOyWjBqR14tJ8", "y": "XVguGFLIZx1fXg3wNqfdbn75hi4-_7-BxhMljw42Ht4"}, "origin": "http://example.com" }
```

with hash:

```
4142d21c00d94ff9b5d504ada8f99b721f4b191ae4e37ca0140f696b6983cfacb
```

and application id:

```
http://example.com
```

with hash:

```
f0e6a6a97042a4f1f1c87f5f7d44315b2d852c2df5c7991cc66241bf7072d1c4
```

to construct a registration request message.

Let's say the U2F token generates the following key pair:

Private key:

```
9a9684b127c5e3a706d618c86401c7cf6fd827fd0bc18d24b0eb842e36d16df1
```

Public key:

```
04b174bc49c7ca254b70d2e5c207cee9cf174820ebd77ea3c65508c26da51b657c1cc6b952f8621697936482da0a6d3d3826a59095daf6cd7c03e2e60385d2f6d9
```

Associated key handle:

```
2a552dfdb7477ed65fd84133f86196010b2215b57da75d315b7b9e8fe2e3925a6019551bab61d16591659cbaf00b4950f7abfe6660e2e006f76868b772d70c25
```

The signature base string for the registration response message is therefore:

```
00f0e6a6a97042a4f1f1c87f5f7d44315b2d852c2df5c7991cc66241bf7072d1c44142d21c00d94ffb9d504ada8f99b721f4b191ae4e37ca0140f696b6983cfac2a552dfdb7
```

A possible signature over the base string with the above private attestation key is:

```
304502201471899bcc3987e62e8202c9b39c33c19033f7340352dba80fcab017db9230e402210082677d673d891933ade6f617e5dbde2e247e70423fd5ad7804a6d3d3961eff
```

Which means the whole registration response message is:

```
0504b174bc49c7ca254b70d2e5c207cee9cf174820ebd77ea3c65508c26da51b657c1cc6b952f8621697936482da0a6d3d3826a59095daf6cd7c03e2e60385d2f6d9402a552c
```

from which (together with challenge and application parameters) the signature base string and signature can be extracted, and verified with the public key from the attestation cert.

8.2 Authentication Example

Let's assume we have a U2F device with private key:

```
ffa1e110dde5a2f8d93c4df71e2d4337b7bf5ddb60c75dc2b6b81433b54dd3c0
```

and corresponding public key:

```
04d368f1b665bade3c33a20f1e429c7750d5033660c019119d29aa4ba7abc04aa7c80a46bbe11ca8cb5674d74f31f8a903f6bad105fb6ab74aefef4db8b0025e1d
```

Example application id:

```
https://gstatic.com/securitykey/a/example.com
```

Example client data:

```
{"typ": "navigator.id.getAssertion", "challenge": "opsXqUifDriAAmWclinfB80e-USY0CgyJHe_Otd7z8o", "cid_pubkey": {"kty": "EC", "crv": "P-256", "x": "HzQwlfXX7Q4S5MtCCnZUNBw3RMzPO9tOyWjBqRl4tJ8", "y": "XVguGFLIZx1fXg3wNqfdbn75hi4-_7-BxhMljw42Ht4"}, "origin": "http://example.com"}
```

Hash of the above client data (challenge parameter):

```
ccd6ee2e47baef244d49a222db496bad0ef5b6f93aa7cc4d30c4821b3b9dbc57
```

Hash of the above application id (application parameter):

```
4b0be934baebb5d12d26011b69227fa5e86df94e7d94aa2949a89f2d493992ca
```

Assuming counter = 1 and user_presence = 1, signature base string is:

```
4b0be934baebb5d12d26011b69227fa5e86df94e7d94aa2949a89f2d493992ca010000001ccd6ee2e47baef244d49a222db496bad0ef5b6f93aa7cc4d30c4821b3b9dbc57
```

A possible signature with above private key is:

```
304402204b5f0cd17534cedd8c34ee09570ef542a353df4436030ce43d406de870b847780220267bb998fac9b7266eb60e7cb0b5eabdf5ba9614f53c7b22272ec10047a923f
```

Authentication Response Message:

```
010000001304402204b5f0cd17534cedd8c34ee09570ef542a353df4436030ce43d406de870b847780220267bb998fac9b7266eb60e7cb0b5eabdf5ba9614f53c7b22272ec
```

The above signature and signature base string can be reconstructed from the authentication response message and the challenge and application parameters, and can be verified with the above public key.

9. Implementation Considerations

Earlier revisions of the FIDO U2F specifications defined the U2F_VERSION command with the following byte layout:

```
CL IN P1 P2 L0 L1 L2 Le
00 03 00 00 00 00 00 00
```

This is not compatible with ISO 7816-4. (Compatible encodings are defined earlier in this document.)

For maximum compatibility with U2F Authenticators that followed the earlier specification for the U2F_VERSION command, U2F Clients may choose to support this older encoding over the HID protocol, the only protocol defined which used this encoding.

A. References

A.1 Normative references

[ECDSA-ANSI]

[Public Key Cryptography for the Financial Services Industry: The Elliptic Curve Digital Signature Algorithm \(ECDSA\), ANSI X9.62-2005](http://webstore.nist.gov/RecordDetail.aspx?sku=ANSI+X9.62%3A2005) American National Standards Institute, November 2005, URL: <http://webstore.nist.gov/RecordDetail.aspx?sku=ANSI+X9.62%3A2005>

[ECMA-262]

[ECMAScript Language Specification](https://tc39.github.io/ecma262/). URL: <https://tc39.github.io/ecma262/>

[FIDOAppIDAndFacets]

D. Balfanz, B. Hill, R. Lindemann, D. Baghdasaryan, *FIDO AppID and Facets v1.0* FIDO Alliance Proposed Standard. URLs:
HTML: <https://fidoalliance.org/specs/fido-u2f-v1.2-ps-20170411/fido-appid-and-facets-v1.2-ps-20170411.html>
PDF: <https://fidoalliance.org/specs/fido-u2f-v1.2-ps-20170411/fido-appid-and-facets-v1.2-ps-20170411.pdf>

[FIDOGlossary]

R. Lindemann, D. Baghdasaryan, B. Hill, J. Hodges, *FIDO Technical Glossary*. FIDO Alliance Implementation Draft. URLs:
HTML: <https://fidoalliance.org/specs/fido-u2f-v1.2-ps-20170411/fido-glossary-v1.2-ps-20170411.html>
PDF: <https://fidoalliance.org/specs/fido-u2f-v1.2-ps-20170411/fido-glossary-v1.2-ps-20170411.pdf>

[RFC2119]

S. Bradner. *Key words for use in RFCs to Indicate Requirement Levels* March 1997. Best Current Practice. URL: <https://tools.ietf.org/html/rfc2119>

[RFC4648]

S. Josefsson, *The Base16, Base32, and Base64 Data Encodings (RFC 4648)*, IETF, October 2006, URL: <http://www.ietf.org/rfc/rfc4648.txt>

[U2FHeader]

J. Ehrensverd, *FIDO U2F HID Header Files v1.0* FIDO Alliance Review Draft (Work in progress.) URL: <https://github.com/fido-alliance/u2f-specs/blob/master/inc/u2f.h>

[WebIDL]

Cameron McCormack; Boris Zbarsky; Tobie Langel. *Web IDL*. 15 December 2016. W3C Editor's Draft. URL: <https://heycam.github.io/webidl/>

A.2 Informative references

[U2FImpCons]

D. Balfanz, *FIDO U2F Implementation Considerations v1.0* FIDO Alliance Review Draft (Work in progress.) URL: <https://fidoalliance.org/specs/fido-u2f-v1.2-ps-20170411/fido-u2f-implementation-considerations-v1.2-ps-20170411.pdf>

[U2FOverview]

S. Srinivas, D. Balfanz, E. Tiffany, *FIDO U2F Overview v1.0* FIDO Alliance Review Draft (Work in progress.) URL: <https://fidoalliance.org/specs/fido-u2f-v1.2-ps-20170411/fido-u2f-overview-v1.2-ps-20170411.pdf>